

MET-L-CHEK COMPANY -- D-70 DEVELOPER -- 6850-01-265-2743

===== Product Identification =====

Product ID:D-70 DEVELOPER

MSDS Date:10/08/1986

FSC:6850

NIIN:01-265-2743

MSDS Number: BGTBG

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAGE:98733

=== Co

ntractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG

/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS
FORMS) (SARA III)
CAS:1344-28-1
RTECS #:BD1200000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:PER MANUFACTURER,
MAY CAUSE SLIGHT
IRRITATION TO SKIN ON CONTACT AND RESPIRATORY TRACT SYSTEM.
Explanation of Carcinogenicity:CARCINOGENICITY OF THE PRODUCT FOR OSHA
REQUIREMENTS IS SPECIFIED "YES" BY THE MFR,BUT DID NOT SPECIFIED
THE COMPONENT.
Effects of Overexposure:EYES:PRESUMED NON-IRRITATING;SKIN:SLIGHT
IRRITATION ON LIQUID CONTACT;INHALATION:VAPORS OR OIL MIST MAY
CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT;INGESTION:NOT
KNOWN TO MANUFACTURER.
Medical Cond Aggravated by Exposur
e:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER.GET MEDICAL HELP IF IRRITATION OCCURS
OR PERSISTS; SKIN:FLUSH WITH WATER.WASH WITH WATER & SOAP.GET MED
ATTN FOR PERSISTING IRRITATION; INHALATION:REMOVE TO FRESH
AIR.PROVIDE OXY GEN IF BREATHING IS DIFFICULT,GET MED ATTN IF
NEEDED; INGESTION:INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:53F (11.6C)

Lower Limits:2

Upper Limits:12

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO NOT USE DIRECT STREAM OF WATER.

Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:EXPOSED CONTAINERS MAY RUPTURE OR EXPLODE IN HEAT OF FIRE DUE TO BUILDUP IN VAPOR PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGNITION SOURCES.WEAR APPROPRIATE PROTECTIVE CLOTHING & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND OR OTHR MATL.PLACE RAGS & ABSORBED WASTE MATERL I N COVERED NON-LEAKING CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT/IGNITION

SOURCES.STORE IN DRY,COOL & VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING MATERIAL.AVOID PHYSICAL DAMAGE TO CANS.

Other Precautions:MINIMIZE SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR IF EXPOSURE EXCEEDS TLV LIMITS.

Ventilation:PER MFR,EXPLOSION PROOF TO MAINTAIN TLV.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:GOGGLES.

Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS.

Work Hygienic Practices:WASH WITH SOAP & WATER BEFORE EATING,DRINKING,SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

NSN FOR TYPE II,FORM D DEVELOPER OF MIL-I-25135D;QPL-25135-15 SPECIFIED THAT 3 DEVELOPERS ARE QUALIFIED DEVELOPER UNDER TYPE II,FORM D OF MET-L-CHEK COMPANY;THE MFR MAY SUPPLY ONE OF THE FOLLOWING:(1) D-70, (2) D-701, OR (3) D-703 DEVELOPER.THIS ENTRY IS OF D-70 DEVELOPER.THIS PRODUCT IS NOT ALLOWED IN AEROSOL

CANS.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=82.2C, 180.F

Vapor Pres:33@68F

Vapor Density:2.1

Spec Gravity:0.8

Evaporation Rate & Reference:1.4(BUTYL ACETATE)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WHITE,MILKY SUSPENSION,MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL.

Stability Condition to Avoid:HEAT & IGNITION SOURCES.

Hazardous Deco

mposition Products:CARBON MONOXIDE & OTHER UNIDENTIFIED
ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS EPA HAZARDOUS WASTE

#D001,IGNITABLE WASTE.PLACE WASTE MATERIAL IN AN APPROPRIATE
DISPOSAL FACILITY, OR DISPOSE OF IN COMPLIANCE WITH FEDERAL,STATE &
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the De
partment

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.