View NSN Online: https://aerobasegroup.ae/nsn/6850-01-263-2261

MET-L-CHEK COMPANY -- FP-91B PENETRANT, FLUORESCENT -- 6850-01-263-2261

Product ID: FP-91B PENETRANT, FLUORESCENT MSDS Date:10/15/1986 FSC:6850 NIIN:01-263-2261 MSDS Number: BGVLF === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID STREET **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 **Emergency Phone Num:21** 3-450-1111 CAGE:98733 === Contractor Identification === Company Name:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733

Ingred Name:DISTILLATE (PETROLEUM),HYDROTREATED MIDDLE; NOTE: ON MSDS, MFR SIMPLY STATED AS "PETROLEUM HYDROCARBON" FOR ABOVE CAS #. CAS:64742-46-7 RTECS #:JN9379645 OSHA PEL:5 MG/CUM ACGIH TLV:5 MG/CUM

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: MAY CAUSE SLIGHT SKIN IRRITATION; VAPORS OR OIL MIST MAY CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT. Effects of Overexposure: EYES: MAY CAUSE IRRITATION; SKIN: SLIGHT IRRITATION ON CONTACT WITH LIQUID; INHALATION: VAPORS OR MIST OF PRODUCT MAY CAUSE MILD IRRITATION OF UPPER **RESPIRATORY TRACT. CAN** CAUSE CENTRAL NERVOUS SYSTEM DE PRESSION. INGESTION: MAY RESULT IN VOMITING. ASPIRATION MUST BE AVOIDED. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. First Aid: EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION OCCURS OR PERSISTS; SKIN:FLUSH WITH WATER.WASH WITH LUKE WARM WATER & SOAP.GET MEDICAL HELP FOR PERSISTING IRRITATION; INHA LATION: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT.GET MEDICAL ASSISTANCE IF NEEDED; INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING.GET MEDICAL ASSISTANCE. Flash Point Method: PMCC Flash Point:210F/98.9C Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE OR FOAM; DO NOT USE DIRECT STREAM OF WATER ON THE FIRE. **Fire Fighting Proce** dures: IN CONFINED AREA, DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: CONTAINERS MAY BURST AND/OR RUPTURE IN INTENSE HEAT OF FIRE. PER MANUFACTURER, PREHEATED PRODUCT MAY

IGNITE IN AIR WHEN EXPOSED TO FLAME.

Spill Release Procedures: ELIMINATE IGNITION SOURCES. WEAR APPROPRIATE PROTECTIVE CLOTHING AND RESPI

RATORS.SOAK UP WITH ABSORBENT.PLACE WASTE IN SEALED CONTAINERS.FLUSH WITH WATER.LG LIQ:DIKE LIQUID & PUMP INTO SALVAGE TANK.ABS ORB RESIDUE WITH COMM ABSORBENT & PUT IN CLOSED DR
======================================
Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF HEAT/IGNITION.STORE IN COOL,DRY & VENTILATED AREA.DO NOT STORE NEAR OXIDIZING MATERIAL;AVOID PHYSICAL DAMAGE TO CONTAINERS. Other Precautions:MINIMIZE SKIN CONTACT.AVOID BR EATHING VAPORS.
======================================
Respiratory Protection:NOT NEEDED IN NORMAL CONDITIONS OR USES WHEN VAPORS/MIST CONCENTRATIONS ARE BELOW TLV/PEL LIMITS. WEAR NIOSH APPROVED ORGANIC TYPE RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR BELOW TLV LIMITS. Protective Gloves:CHEMICAL RESISTANT Eye Protection:SAFETY GLASSES OR SPLASH-PROOF GOGGLES Other Protec tive Equipment:CHEMICAL RESISTANT APRON TO PREVENT CLOTHING/SKIN CONTACT. Work Hygienic Practices:WASH HANDS WITH SOAP & WATER BEFORE EATING, SMOKING OR USING TOILET FACILITIES;DO NOT EAT/DRINK IN VAPOR CONTMNTD AREA. Supplemental Safety and Health NSN FOR TYPE I,METHOD A,LEVEL 2 OF MIL-I-25135,REV D; PER QPL-25135-15 FP-91B AND FP-92B PENETRANTS ARE LISTED AS QUALIFIED PRODUCTS. THE MFR MAY SUPPLY ONE OF THESE PENETRANTS FOR THIS NSN. THIS ENTR Y DESCRIBES FP-91B PENETRA
======================================
HCC:N1 Boiling Pt:B.P. Text:>400F/>204C Spec Gravity:ABOUT 0.86 Solubility in Water:INCOMPLETE Appearance and Odor:YELLO-GREEN LIQUID. SLIGHT HYDROCARBON ODOR.
======================================
Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL

Stability Condition to Avoid:SOURCE OF HEAT/IGNITION. AVOID EXPOSURE TO OXIDIZING MATERIALS.

Hazardous Decomposition Products:CAN

OXIDES OF CARBON (CARBON MONOXIDE, CARBON DIOXIDE) AND OTHER UNIDENTFIED ORGANIC COMPOUNDS.

Waste Disposal Methods:PER MANUFACTURER, THE WASTE CAN BE INCINERATED OR DISPOSED OF AS EPA HAZARDOUS WASTE #D001,IGNITABLE WASTE, IN FULL COMPLIANCE WITH ALL FEDERAL STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.