

DOW CORNING CORP -- 93-096-1/2 CURING AGENT -- 8030-00-216-5345

=====
Product Identification
=====

Product ID:93-096-1/2 CURING AGENT

MSDS Date:09/19/1989

FSC:8030

NIIN:00-216-5345

Kit Part:Y

MSDS Number: BGVZR

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Prepa

er's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES-MAY CAUSE TEMPORARY DISCOMFORT.
SKIN-SEVERAL REPEATED, PROLONGED EXPOSURES MAY CAUSE SLIGHT
IRRITATION. INHALATION-NO IRRITATION TO NOSE OR THROAT EXPECTED.
ORAL-AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, ETC., DURING
NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

Explanation

of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT
UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.

Medical Cond Aggravated by Exposure:THIS PRODUCT AS WITH ANY CHEMICAL,
MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW
OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO
THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER.

SKIN: WIPE OFF & FLUSH WITH WATER.

INHALATION: NO PROBLEM. ORAL: NO PROBLEM.

=====
Fire Fighting Measures
=====

Flash Point Method:OC

Flash Point:>250F/121C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING
CHEMICALS.

Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE PRODUCT & USE ABSORBENT MATERIAL TO
TAKE CARE OF ANY OIL-LIKE RESIDUES.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 90F/32C. USE REASONABLE
CARE.

Other Precautions:COMMENTS: TRACES OF FORMALDEHYDE AND OTHER THERMAL
DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 150C IN THE
PRESENCE OF AIR. PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT

ELEVATED TEMPERATURE S.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GENERAL MECHANICAL VENTILATION IS RECOMMENDED.

Protective Gloves:WASHING AT MEALTIME & END OF SHIFT.

Eye Protection:SAFETY GLASSES, AS A MINIMUM.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:GOOD PRACTICE REQUIRES THAT GROSS AMOUNTS OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL.

Suppleme

ntal Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: