

NATIONAL WELDING ALLOYS, INC. -- 5356 ALUMINUM -- 3439-01-012-6661

=====
Product Identification
=====

Product ID:5356 ALUMINUM

MSDS Date:11/10/1986

FSC:3439

NIIN:01-012-6661

MSDS Number: BGWFM

=== Responsible Party ===

Company Name:NATIONAL WELDING ALLOYS, INC.

Address:1600 SOUTH CANAL STREET

City:PITTSBURGH

State:PA

ZIP:15215

Country:US

Info Phone Num:412-781-4255

Emergency Phone Num:412-781-4255

CAGE:0ACE2

=== Contractor Identification ===

Company Name:NATIONAL WELDING ALLOYS INC

Address:1600 SOUTH CANAL STREET

Box:City:PITTSBURGH

State:PA

ZIP:15215-2624

Country:US

Phone:412-781-4255

CAGE:0ACE2

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 93-94%

Other REC Limits:NONE

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:MAGNESIUM

CAS:7439-95-4

RTECS #:OM2100000

Ot

her REC Limits:NONE

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.4%
Other REC Limits:NONE
OSHA PEL:10MG/M³(FE*2O*3)
ACGIH TLV:15MG/M³(FE*2O*3)

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 0.25%
Other REC Limits:NONE
OSHA PEL:15 MG/M³ TDUST
ACGIH TLV:10 MG/M³ TDUST; 9293

Ingred Name:TITANIUM
CAS:7440-32-6
RTECS #:XR1700000
Fraction by Wt: .06-20%
Other REC Limits:NONE
OSHA PEL:10MG/M³(TIO*2)
ACGIH TLV:10MG/M³(TIO*2)

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: .05-.20%
Other REC Limits:NONE
OSHA PEL:1 MG/M³
ACGIH TLV:0.5 MG/M³; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Other REC Limits:NONE
OSHA PEL:(C) 5 MG/M³ DUST
ACGIH TLV:5 MG/M³ DUST 9293

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.1%
Other REC Limits:NONE
OSHA PEL:0.1MG/M³ FUME/1 DUST
ACGIH TLV:0.2MG/M³ FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt

Qty:5000 LBS

Ingred Name:ZINC (SARA III)

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 0.1%

Other REC Limits:NONE

OSHA PEL:10 MG ZNO/M3

ACGIH TLV:10 MG ZNO/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:OTHER TOTAL

Fraction by Wt: 0.15%

Other REC Limits:NONE

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUT

E:METALLIC TASTE,NAUSEA,TIGHTNESS

OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.

CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG

FIBROSIS,PNEUMOCONIOSIS.

Explanation of Carcinogenicity:CHROMIUM IS LISTED UNDER NTP AND IARC.

Effects of Overexposure:METALLIC TASTE, NAUSEA, TIGHTNESS OF CHEST,

FEVER, DIZZINESS, DRYNESS, IRRITATION OF EYES, NOSE AND THROAT.

Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS.HI

GHYER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

=====
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF
NOT BREATHING,GIVE CPR.IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRST AID
TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:FIRE

FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:WELDING ARCS AND SPARKS CAN IGNITE COMBUTIBLE PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DOT APPROVED DISPOSAL CONTAINER.

===== Handling and Storage =====

Other Precautions:TRAIN WELDER TO KEEP HIS OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO MAINTAIN BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Pr

tection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT,SHOULDER PROTECTION.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKE,USING SANITARY FACILITIES.

Supplemental Safety and Health NONE.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ROD.NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: FUMES OF METALS AND METALS
OXIDES, CO, NO₂, O₃.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF FUMES, FLUX OR WELD GRINDING RESIDUE
FROM THE WORK AREA OR FROM FILTERS IAW ALL APPLICABLE FEDERAL, STATE
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.