

AKZO COATINGS INC./AEROSPACE FINISHES DIV. -- CURING SOLN(CA-97) FOR 463-6 RESIN/IN KIT
-- 1615-01-115-3616

===== Product Identification =====

Product ID:CURING SOLN(CA-97) FOR 463-6 RESIN/IN KIT

MSDS Date:10/31/1988

FSC:1615

NIIN:01-115-3616

Kit Part:Y

MSDS Number: BGWFS

=== Responsible Party ===

Company Name:AKZO COATINGS INC./AEROSPACE FINISHES DIV.

Address:434 W. MEATS AVE

City:ORANGE

State:CA

ZIP:92665

Country:US

Info Phone Num:313-855-7313 AFTER HOURS

Emergency Phone Num:313-589-3660(8 AM 4:45 PM E.S.T.)

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

Company Name:BOEING HELICOPTERS, DIV OF THE BOEING CO

Address:BOEING CENTER, INDUSTRIAL HWY BLDG 3-25

Box:City:RIDLEY PARK

State:PA

ZIP:19078

Country:US

Phone:215-591-3010

CAGE:7727

=====
 ===== Composition/Information on Ingredients =====
 =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 40.-55%.

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 45.-60%.

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
 ===== Hazards Identification =====
 =====

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE IRRITANT,CONTACT MAY CAUSE
 EYE BURNS OR CORNEAL INJURY. EXCESSIVE INHALATION OF VAPORS CAN
 CAUSE NASAL & RESPIRATORY

IRRITATION,DIZZINESS,WEAKNESS,FATIGUE,NAUSEA,ETC.; CHRONIC:REPEATED
 OVERE XPOSURE MAY RESULT IN DELAYED KIDNEY INJURY, ALSO POSSIBLE
 LIVER ABNORMALITIES.

Effects of Overexposure:EYE:IRRITANT,TEARING,BLURRED
 VISION,REDNESS,BURN O

R CORNEAL INJURY; SKIN: DERMATITIS & MILD

IRRITATION; INHAL: NASAL & RESPIRATORY IRRITATION, DIZZINESS,
 WEAKNESS, HEADACHE, POSSIBLE UNCONSCIOUSNESS & EVEN ASPHYXIATION;
 INGEST: MAY CAUSE G.I. IRRITATION, NAUSEA, VOMITING & DIARRHEA.

Medical Cond Aggravated by Exposure:NONE EXPECTED.

=====
 ===== First Aid Measures =====
 =====

First Aid:EYE: FLUSH W/WATER FOR AT LEAST 15 MINS.GET MEDICAL ATTN.;

SKIN: WASH W/ SOAP & WATER; INHAL:MOVE TO FRESH AIR. GIVE

ARTIFICIAL RESPIRATION IF NECESSARY; INGEST: DRINK ONE OR TWO GLASSES OF WATER TO DILUTE. DONOT INDUCE VOMITING. GET MEDICAL ATTN IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:40F/4.4C

Lower Limits:1.2

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE. FIRE FIGHTING PERSONNEL SHOULD

WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS,ELECTRICAL EQUIPMENT & OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REVIEW: A)FIRE & EXPLOSION HAZARD;

B)REACTIVITY; C)HEALTH HAZARD; D)SAFE HANDLING & USE INFORMATION; & E)SPECIAL PRECAUTION SECTORS. REMOVE ALL IGNITION

SOURCES. AVOID

BREATHING VAPORS. VENTILATE AREA . REMOVE SPILLED MATERIAL W/ INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS OUT OF SUN & AWAY FROM HEAT, SPARKS & OPEN FLAMES. CLOSE CONTAINERS AFTER EACH USE. CONSULT N.F.P.A. CODE FOR ADDITIONAL STORAGE REQS

Other Precautions:DONOT TAKE INTERNALLY. USE APPROVED BONDING & GROUNDING PROCEDURES. OBSERVE LABEL PRECAUTIONS. KEEP CLOSURES

TIGHT & CONTAINER UPRIGHT TO PREVENT LEAKAGE. NEVER USE PRESSURE TO EMPTY-DRUM IS NOT A PRESSURE VESSEL.DONOT WELD OR FLAME CUT!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE. SEE YOUR SAFETY EQUIPMENT SUPPLIER FOR EVALUATION & RECOMMENDATION. IN CONFINED AREAS, USE NIOSH/MSHA APPROVED AIRLINE RESPIRATOR OR HOOD.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO KEEP VAPOR CONCENTRATION BELOWS

GIVEN TLV & LEL.FOR BAKING FINISHES, EXHAUST VAPORS.

Protective Gloves:NON-PERMEABLE TYPE FOR TASK AT HAND.

Eye Protection:TYPE DESIGNED TO PROTECT AGAINST SPLASH.

Other Protective Equipment:EYE BATH & SHOWER SHOULD BE AVAILABLE. USE
CHEMICAL RESISTANT APRON, BOOTS OR OTHER CLOTHING TO AVOID SKIN
CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR PERFORMING
OTHER DUTIES.

Supplemental Safety and Health

MFR CODE: CA97; HAZ CHAR CODE IS FOR OVERALL KIT, FOR THIS PART

KEY1:

F2; PART 4 OF 9 PARTS PUT TOGETHER BY BOEING HELICOPTERS UNDER MFR
DRAWING 114RK651-2.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=82.2C, 180.F

B.P. Text:180-498F(RG

Vapor Density:>1.

Spec Gravity:0.84

Evaporation Rate & Reference:(ETHER=1);SLOWER THAN

Percent Volatiles by Volume:92.2

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE.

Hazardo

us Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SMOKE

& OXIDES OF NITROGEN.(DURING EMERGENY,OVEREXPOSURE TO PRODUCTS MAY
AFFECT HEALTH)

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN AN APPROVED FACILITY; DONOT
INCINERATE CLOSED CONTAINERS. DISPOSE OF I/A/W FEDERAL,STATE &
LOCAL POLLUTION CONTROL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):

This information is formula

ted for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.