View NSN Online: https://aerobasegroup.com/nsn/8010-00-257-5374

Product ID:LACQUER C/N GLOSS 11 PURPLE 27144 ID786708 MSDS Date:12/15/1988 FSC:8010 NIIN:00-257-5374 MSDS Number: BHBWZ === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name:W.A . ELLISON CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:ISOBUTYL ACETATE (SARA III) CAS:110-19-0 RTECS #:AI4025000 OSHA PEL:150 PPM ACGIH TLV:150 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ISOP

ROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE CAS:9004-70-0 RTECS #:QW0970000 OSHA PEL:NONE ESTABLISHED ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:NAPHTA (PETRO LEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:DE3030000 OSHA PEL:100 PPM

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III) CAS:117-81-7 RTECS #:TI0350000 OSHA PEL:5 MG/M3/10 STEL ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:ALIPHATIC HYDROCARBON (VP MM HG @ 20 DEG C 12) CAS:64742-89-8 OSHA PEL:NONE ESTABLISHED ACGIH TLV:NONE ESTABLISHED

Ingred Name:VOL ORGANIC CMPD 5.0 LB/GL LESS WATER & NPRS\* 600 G/L LESS WATER VOC 18.5 LB/GAL SO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION,NAUSEA AND VOMITING. INHALATION:MAY CAUSE NOSE OR THROAT IRRITATION. EYE:MAY CAUSE EYE IRRITATION. SKIN:MAY CAUSE DEFATTING AND IRRITATION OF THE SKIN. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM.

Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE C ONTENTS MAY BE HARMFUL OR FATAL.

First Aid:SWALLOWING:DO N OT INDUCE VOMITING. GET MED ATTN:

INHALATION:REMOVE TO FRESH AIR IMMED AND GET MED ATTN. EYE:FLUSH WITH LARGE AMOUNTS OF WATER AT LEAST 15 MIN. GET MED ATTN. SKIN:FLUSH THE CONTAMINATED AREA WITH WATER. REMOVE CLOTHING CONSULT A PHYSICIAN. NOTE TO PHYSICIAN ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS

Flash Point:20F/-6

.67C

Extinguishing Media:CLASS B FIRE EXTINGUISHERS.POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WTR MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS. IF WTR USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:DURING EMERGENCY COND OVEREXP TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.OBTAIN MEDICAL ATTN.WARNING:FLAMMABLE

\_\_\_\_\_

Spill Release Procedures: ELIMINATE IGNITION SOURCES. USE ONLY NON-SPARKING TOOLS. DIKE WITH INERT MATERIAL. PUT IN METAL CONTAINERS FOR DISPOSAL.PREVENT CONTAMINATION OF SEWER, STREAMS, AND GROUNDWATER.

Handling and Storage Precautions:DO NOT STORE ABOVE 95F.STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT TAKE INTERNALLY. C
LOSE CONTAINER AFTER EACH USE. DO NOT REUSE CONTAINERS.CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE/CUT ON CONTAINER.NEVER USE PRESSU RE TO EMPTY.

Respiratory Protection:RESTRICTED VENTILATION A NIOSH CHEMICAL RESPIRATOR MAY BE REQUIRED. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR RESPIRATOR. REFER TO OSHA 29CFR1910.134 AND RESPIRATORY PROTECTION A MANUAL AND GUIDEL INE, AMER IND HYGIENE ASSOC. Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN TO MAINTAIN CONCENTRATIONS. Protective Gloves:SOLVENT IMPERMEABLE GLOVES. Eye Protection:WEAR SAFETY SPECTACLES. Other Protective Equipment:NOT LIKELY TO BE NEEDED. Supplemental Safety and Health NONE LISTED.

Boiling Pt:B.P. Text:180F/302F Vapor Density:>AIR Evaporation Rate & amp; Ref erence:SLOWER THAN ETHER Percent Volatiles by Volume:73

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE. IN ADDITION OXIDES OF NITROGEN MAY BE GEN.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT,

Waste Disposal Methods:DISPOSE IAW FEDERAL,STATE AND LOCAL LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. MATERIAL TO BE DISPOSED OF IN A HAZARDOUS WASTE LANDFILL. RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Stat

es of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.