

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS 41 BROWN 10080 ID742012 --
8010-00-286-7737

=====
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS 41 BROWN 10080 ID742012

MSDS Date:03/22/1988

FSC:8010

NIIN:00-286-7737

MSDS Number: BHCNC

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-7

33-1361

Emergency Phone Num:716-873-6000

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SPIRITS (VP MM HG @ 20 DEG C 2)

CAS:64475-85-0

RTEC

S #:PY8240000
OSHA PEL:500 PPM 2950 MG/CUM
ACGIH TLV:100 PPM 525 MG/CUM

Ingrd Name:VOL ORGANIC CMPD 3.9 LB/GL LESS WATER & NPRS* 468 G/L LESS
WATER VOC 9.8 LB/GAL SOLIDS 1176 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING-DO NOT INDUCE VOMITING.GET
MED ATTN:INHALATION-MOVE TO FRESH AIR, KEEP WARM & QUIET, GET MED
ATTN:EYE-FLUSH WITH LARGE AMOUNTS OF WATER.GET MED ATTN.
SKIN-REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA. NOTE TO
PHYSICIAN: OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF
SYMPTOMS AND THE CLINICAL COND.
Explanation of Carcinogenicity:NONE LISTED
Effects of Overexposure:PROLONGED & REPEATED OCCUPATION OVEREXPOSURE TO
SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. DELIBERATE
CONCENTRATIONS & INHALING MAY BE FATAL.HIGH CONCENTRATIONS MAY
CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY
HEADACHES,DIZZINESS,NAUSEA AND CONFUSION.
Medical Cond Aggravated by Exposure:NONE LISTED.

=====
===== First Aid Measures =====

First Aid:SWALLOWING:DO NOT INDUCE VOMITING. INHALATION-REMOVE TO FRESH
AIR. EYE-FLUSH WITH LARGE AMOUNTS OF WATER.GET MEDICAL ATTN ON ALL
OF THE ABOVE. SKIN-REMOVE CONTAMINATED CLOTHING, WASH BEFORE
RE-USE. IF IRRITATION PERSISTS SEEK MEDICAL ATTN.ANY TREATMENT
THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE
CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

=====
===== Fire Fighting Measures =====

Flash Point:102F/48.89C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS FOR FLAMMABLE LIQUID
FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT

T PRESSURE

BUILD-UP/AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO HEAT.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT/ELECTRICAL

EQUIPMENT/SPARKS/FLAME. KEEP CONTAINERS CLOSED.OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.OBTAIN MED ATTN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DIKE WITH INERT MATERIAL. PUT IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. USE ONLY NON-SPARKING T

TOOLS. PREVENT CONTAMINATION OF

SEWERS/STREAMS/GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. RCRA CLASSIFICATION WOULD BE D001. NO KNOWN ENVIRONMENTAL HAZ.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT WELD/BRAZE/CUT ON EMPTY CONTAINER. DO NOT RE-USE ANY CONTAINERS. NEVER USE PRES

SURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. IN CONFINED AREAS USE A NIOSH/MSHA AIR SUPPLIED RESPIRATOR. REFER TO OSHA 29CFR1910.134.

Ventilation:GENERAL DILUTION & LOCAL EXHAUST VENTILATION. REMOVE DECOMPOSITION PRO

D THAT ARE GENERATED WHEN WELDING/CUTTING/BRAZING.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Supplemental Safety and Health

NONE LISTED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:280F/388F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE IN EPA PERMITTED FACILITY.

CO

CONTAMINATED ABSORBANT MAY BE DISPOSED OF IN A HAZARDOUS WASTE LANDFILL. DISPOSE IAW FED/ST/LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disc

claims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.