

PACKAGING SERVICE CO., INC. -- BOILED LINSEED OIL -- 8010-00-242-6114

=====  
Product Identification  
=====

Product ID:BOILED LINSEED OIL

MSDS Date:11/01/1987

FSC:8010

NIIN:00-242-6114

MSDS Number: BHDGP

=== Responsible Party ===

Company Name:PACKAGING SERVICE CO., INC.

Address:4704 SHANK ROAD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Info Phone Num:(713) 485-1457

Emergency Phone Num:(713)

485-1457

Preparer's Name:SCIENTIFIC INFO SERVICES

CAGE:9V846

=== Contractor Identification ===

Company Name:PACKAGING SERVICES INC

Address:472 SHANK RD

Box:875

City:PEARLAND

State:TX

ZIP:77581

Country:US

Phone:713-485-1457

CAGE:9V846

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BOILED LINSEED OIL

CAS:67746-08-1

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogeni

city:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: POSSIBLY A MILD IRRITANT TO SKIN

Effects of Overexposure:SKIN: IRRITATION DEVELOPS SLOWLY AFTER CONTACT.  
EYE: IRRITATION DEVELOPS IMMEDIATELY UPON CONTACT.

===== First Aid Measures =====

First Aid:INGESTION: DONOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. EYES: FLUSH WITH WATER FOR 15 MINUTES, GET MEDICAL ADVICE. SKIN: WASH WITH SOAP AND WATER  
. GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP ANDPERSIST.

===== Fire Fighting Measures =====

Flash Point:200F/33.89C

Extinguishing Media:WATER FOG, SPRAY, FOAM, DRY POWDER, CO2

Fire Fighting Procedures:APPROACH FIRE FROM UPWIND SIDE. AVOID BREATHING SMOKE,FUMES,MIST, OR VAPORS. WATER MAY CAUSE FROTHING IF DIRECTED INTO CONTAINERS OF BURNING LIQUID.

Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE FROM INTERNAL PRESS IF CONFINED TO FIRE AREA.

COOL WITH WATER. EVACUATE PERSONNEL FROM THE AREA.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS, PICK UP WITH ABSORBENT MEDIA. STORE AS INDUSTRIAL WASTE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM OXIDIZERS OR MATERIALS BEARING A YELLOW DOT LABEL.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respir

atory Protection:NOT NORMALLY NEEDED

Ventilation:LOCAL EXHAUST OR MECHANICAL IS DESIRED

Protective Gloves:NEOPRENE RUBBER TYPE RECOMMENDED

Eye Protection:CHEMICAL GOGGLES W/FULL FACESHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING, OR SMOKING.  
IF CONTACT OCCURS REMOVE CONTAMINATED CLOTHING & WASH BEFORE  
REUSE.

Supplemental Safety and Health

NK

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Me

It/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:0.92

Evaporation Rate & Reference:NA

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR YELLOW LIQUID W/DISTINCT ODOR

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS OR OXIDIZING MATERIALS

Hazardous Decomposition Products:CARBON DIOXIDE/MONOXIDE, POSSIBLY  
ACROLEIN

=====  
===== Disposal Considerations =====

Wast

e Disposal Methods:EPA APPROVED INDUSTRIAL WASTE DISPOSAL SITE.  
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.