

LIQUID AIR CORPORATION -- ACETYLENE -- 6830-00-270-8216

===== Product Identification =====

Product ID:ACETYLENE

MSDS Date:10/01/1985

FSC:6830

NIIN:00-270-8216

MSDS Number: BHDFZ

=== Responsible Party ===

Company Name:LIQUID AIR CORPORATION

Address:2121 N. CALIFORNIA BLVD., SUITE 350

City:WALNUT CREEK

State:CA

ZIP:94596

Country:US

Info Phone Num:415-977-6500

Emergency Phone Num:800-434-9300 OR NIGH

T 800-231-1366

CAGE:DO426

=== Contractor Identification ===

Company Name:INTERSTATE WELDING SALES CORP.

CAGE:14135

Company Name:LIQUID AIR CORP ONE CALIFORNIA PLAZA

Address:2121 N. CALIFORNIA BLVD

Box:City:WALNUT CREEK

State:CA

ZIP:94596

Country:US

Phone:415-977-6500

CAGE:18260

Company Name:LIQUID AIR CORPORATION

Address:2121 N. CALIFORNIA BLVD., SUITE 350

City:WALNUT CREEK

State:CA

ZIP:94596

Phone:510-977-6500

CAGE:DO426

===== Composition/Information on Ingredients =====

I

ingred Name:ACETYLENE
CAS:74-86-2

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:REPEATED EXPOSURES TO TOLERABLE LEVELS
HAS NOT SHOWN DELETERIOUS EFFECTS. THE MAJOR PROPERTY IS THE
EXCLUSION OF AN ADEQUATE SUPPLY OF OXYGEN TO THE LUNGS
Explanation of Carcinogenicity:ACETYLENE IS DEFINED AS A SIMPLE
ASPHYXIANT.
Effec
ts of Overexposure:INHALATION: LOW CONCENTRATION (10-20% IN AIR)
CAUSE SYMPTOMS SIMILAR TO THAT OF BEING INTOXICATED. HIGHER
CONCENTRATIONS SO AS TO EXCLUDE AN ADEQUATE SUPPLY OF OXYGEN TO THE
LUNGS CAUSE UNCONSCIOUSNES S.

===== First Aid Measures =====

First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF
OVEREXPOSURE TO ACETYLENE.RESCUE PERSONNEL SHOULD BE EQUIPPED
W/SELFCONTAINED BREATHING APPARATUS & BE COGNIZANT OF EXTREM
E
FIRE & EXPLOSION HA ZARD. INHALATION: CONSCIOUS PERSONSSHOULD BE
ASSISTED TO AN UNCONTAMINATED AREA & INHALE FRESH AIR. QUICK
REMOVAL FROM CONTAMINATED AREA IS MOST IMPORTANT.UNCONSCIOUS
PERSONS GIVE RESUSCITATION.

===== Fire Fighting Measures =====

Flash Point:GAS
Autoignition Temp:Autoignition Temp Text:****
Lower Limits:80-85
Upper Limits:2.2
Extinguishing Media:CARBON DIOXIDE; DRY CHEMICAL
Fire Fighting Procedures:IF POSSIBLE STOP FLOW O
F ESCAPING GAS. USE
WATER SPRAY TO COOL SURROUNDING CONTAINERS. KEEP PERSONNEL
AWAY SINCE HEATED/BURNING CYLINDERS CAN RUPTURE.
Unusual Fire/Explosion Hazard:IT REQUIRES A VERY LOW IGNITION ENERGY SO
THAT FIRES WHICH HAVE BEEN EXTINGUISH W/O STOPPING FLOW OF GAS CAN
EASILY REIGNITE W/POSSIBLE EXPLOSIVE FORCE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE
APPROPRIATE PROTECTIVE

EQUIP. IF LEAK IS IN USER'S EQUIP., BE CERTAIN TO PURGE PIPING W/INERT GAS PRIOR TO ATTEMPTING REPAIRS. IF LEAK IS IN CONTAINER OR CONTAINER VALVE CONTACT CLOSEST LIQUID AIR CORP.

=====
===== Handling and Storage =====

Handling and Storage Precautions: USE SUITABLE HANDTRUCK FOR CYLINDER MOVEMENT. STORE IN COOL, DRY, WELL VENTILATED AREA OF NONCOMBUSTIBLE CONSTRUCTION AWAY FROM HEAVY TRAFFICKED AREAS.

Other Precautions: FULL & EMPTY CYLINDERS SHOULD BE SEGREGATED.

CYLINDERS MUST BE STORED IN UPRIGHT & FIRMLY SECURED TO PREVENT FALLING/KNOCKED OVER. EARTH-GROUND & BOND ALL LINES & EQUIPMENT ASSOCIATED W/ACETYLENE SYSTEM.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: POSITIVE PRESSURE AIR LINE W/MASK OR SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR EMERGENCY USE.

Ventilation: HOOD W/FORCED VENTILATION. LOCAL EXHAUST TO PREVENT ACCUMULATION ABOVE THE LEL.

P

Protective Gloves: PVC OR RUBBER

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: SAFETY SHOES, SAFETY SHOWERS

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: -118.8F

Vapor Pres: 645 PSIA

Vapor Density: .0691

Solubility in Water: COEFFICIENT = 1.047

Appearance and Odor: PURE ACETYLENE: COLORLESS GAS W/ETHEREAL ODOR.

COMMERCIAL: GARLIC LIKE ODOR

Percent Volatiles by Volume: 30 PSIA

=====
===== Stab

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

OXYGEN/ODIDIZERS INCLUDING ALL OF THE HALOGENS/COMPOUNDS.

COPPER,MERCURY,SILVER,BRASSES/BRAZING CONTNING 66% COPR/SLVR

Stability Condition to Avoid:DONOT ALLOW FREE GAS (OUTSIDE OF CYLINDER)

TO EXCEED 30PSIA.CYLINDERS SHOULD NOT BE EXPOSED TO SUDDEN

SHOCK/SOURCES HEAT

Hazardous Decomposition Products:CARBON AND HYDROGEN

===== Disposal Considerations =====

Waste

Disposal Methods:DONOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED QTY.

RETURN IN SHIPPING CONTAINER PROPERLY LABELED, W/VALVE OUTLET

PLUGS OR CAPS SECURED & VALVE PROTECTION CAP IN PLACE TO

LIQUID AIR CORPORATION FOR PROPER DISPOSAL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this in

formation to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.