

EVERSEAL MANUFACTURING CO., INC. -- DARK BLUE GLOSS ALKYD ENAMEL 15044 --
8010-00-298-2302

===== Product Identification =====

Product ID:DARK BLUE GLOSS ALKYD ENAMEL 15044
MSDS Date:10/21/1987
FSC:8010
NIIN:00-298-2302
MSDS Number: BHDKZ
=== Responsible Party ===
Company Name:EVERSEAL MANUFACTURING CO., INC.
Address:475 BROAD AVENUE
City:RIDGFIELD
State:NJ
ZIP:07657
Country:US
Emergency Phone Nu
m:201-943-4986
CAGE:EO432

=== Contractor Identification ===
Company Name:EVERSEAL MANUFACTURING CO., INC.
CAGE:EO432
Company Name:EVERSEAL MFG CO INC
Address:475 BROAD AVE
Box:City:RIDGFIELD
State:NJ
ZIP:07657-2329
Country:US
Phone:201-943-4986
CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN
Fraction by Wt: 35%

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 2%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 92

Ingred Name:COMPLEX ORGANIC BLUE
 CAS:14038-43-8
 Fraction by Wt: 7%
 OSHA PEL:AS DUST 10 MG/M3
 ACGIH TLV:NA

Ingred Name:MINERAL SPIRITS
 VAPOR PRESSURE 2
 CAS:64742-88-3
 Fraction by Wt: 52%
 OSHA PEL:120 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
 Effects of Overexposure:INHALATION DIZZINESS,NAUSEA,POSSIBLE
 UNCONSCIOUSNESS.IRRITATION TO SKIN & EYES.

===== First Aid Measures =====

First Aid:INHALATION REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION
 IF NECESSARY.SKIN WASH W/SOAP & WTR.EYES FLUSH W/WTR.CONSULT
 PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:105F/40.56C
 Lower Limits:1
 Extinguishing Media:FOAM, CARBON DIOXIDE CO2, DRY CHEMICAL
 Unusual Fire/Explosion Hazard:WATER NOT SUITABLE EXTINGUISHING
 MEDIUM.FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.ENSURE ADEQUATE
 VENTILATION.ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL.USE
 SPARK-PROOF SCOOP FOR LARGER SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOIDE EXCESSIVE HEAT & OPEN IGNITION
 SOURCES.
 Other Precautions:NPCA/HMIS RATING 3,2,0,H.

===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN W/CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323 - 390F

Vapor Density:>AIR

Evaporation Rate & Reference: