

EVERSEAL MANUFACTURING CO., INC. -- BLACK GLOSS ALKYD ENAMEL 17038 -- 8010-00-527-2050

=====
Product Identification
=====

Product ID:BLACK GLOSS ALKYD ENAMEL 17038

MSDS Date:05/26/1987

FSC:8010

NIIN:00-527-2050

MSDS Number: BHDMP

=== Responsible Party ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

Address:475 BROAD AVENUE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Emergency Phone Num:201-94

3-4986

CAGE:EO432

=== Contractor Identification ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

CAGE:EO432

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

=====
Composition/Information on Ingredients
=====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 3%

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:MINERAL SPIRITS

VAPOR PRESSURE

5
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 55%
ACGIH TLV:120 PPM

Ingred Name:RESIN
Fraction by Wt: 41%
OSHA PEL:NA
ACGIH TLV:NA

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:INHALATION: DIZZINESS, NAUSEA, POSSIBLE
UNCONSCIOUSNESS SKIN/EYE: IRRITATION

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR, APPLY ARTI
FICIAL RESPIRATION
IF NECESSARY. EYE: FLUSH WITH WATER
SKIN: WASH WITH SOAP AND WATER.
CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:105F/40.56C
Lower Limits:1
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIREFIGHTERS SHOULD WEAR A SELF CONT-AINED BREATHING
APPARATUS.

=====
Accidental Release Measures
=====

=====
Spill Release Procedures:REMOVE IGNITION SOURCES, ENSURE ADEQUATE
VENTILA- TION. ABSORB SMALL SPILLS ON DRY ABSORPTION MATL. USE
SPARK PROOF SCOOP FOR LARGER SPILLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION
SOURCES.
Other Precautions:NPCA/HMIS RATING 3,2,0,H

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF TLV MAY BE EXCEEDED. USE C

ARTRIDGE MASK

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323-390F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stabi

lity Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NA

Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL AND LOCAL REGULATIONS FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United S

tates of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.