

EVERSEAL MANUFACTURING CO., INC. -- GRAY SEMI GLOSS ENAMEL C26307 -- 8010-00-901-1061  
===== Product Identification =====

Product ID:GRAY SEMI GLOSS ENAMEL C26307  
MSDS Date:10/21/1987  
FSC:8010  
NIIN:00-901-1061  
MSDS Number: BHFSY  
=== Responsible Party ===  
Company Name:EVERSEAL MANUFACTURING CO., INC.  
Address:475 BROAD AVENUE  
City:RIDGFIELD  
State:NJ  
ZIP:07657  
Country:US  
Info Phone Num:201-943-4986

Emergency Phone Num:201-943-4986  
CAGE:EO432  
=== Contractor Identification ===  
Company Name:EVERSEAL MANUFACTURING CO., INC.  
CAGE:EO432  
Company Name:EVERSEAL MFG CO INC  
Address:475 BROAD AVE  
Box:City:RIDGFIELD  
State:NJ  
ZIP:07657-2329  
Country:US  
Phone:201-943-4986  
CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN  
Fraction by Wt: 27%

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 15%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TL

V:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE

CAS:1309-37-1

Fraction by Wt: 2%

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 19%

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN  
1% CRYSTALLINE SILICA

CAS:61790-53-2

RTECS #:HL8600000

Fraction by Wt: 1%

OSHA PEL:20 MPPCF

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MINE

RAL SPIRITS

(VAPOR PRESSURE 5)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 36%

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Effects of Overexposure:INHALATION: MAY CAUSE DIZZINESS, NAUSEA,  
UNCONSCIOUSNESS. PROLONGES OR REPEAT-ED EXPOSURE TO DUST FROM  
SANDING, GRINDING OR BLASTING MAY CAUSE LUNG DISORDERS.EYES: MAY  
CAUSE IRRITATIONSKIN: MAY CA USE IRRITATION

=====  
=== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL  
RESPIRATION IF NECESSARY. SKIN: CLEAN WITH SOAP AND WATER.  
EYES: FLUSH WITH WATER,  
CONSULT PHYSICI AN.

=====  
===== Fire Fighting Measures =====

Flash Point:105F/40.56C

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING  
MEDIUM. FIREFIGHTERS SHOULD WEAR S

ELF- CONTAINED BREATHING  
APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:ENSURE ADEQUATE VENTILATION. REMOVE ALL  
IGNITION SOURCES.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION  
SOURCES.

Other Precautions:NPCA/HMIS RATING 3,2,O,H.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME AND  
DUST MASK OR AIR-SUPPLIED HOOD.

Ventilation:ADEQUATE TO ENSURE LEL NOT ACHIEVED.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323F-390F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:56

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

NK

Stability Condition to Avoid:NA

Hazardous Decomposition Products:CARBON DIOXIDE OR CARBON MONOXIDE WHEN  
COMBUSTED.

===== Disposal Considerations =====

Waste Disposal Methods:USE ABSORPTION MATERIAL FOR SMALL SPILLS. USE  
SPARK-PROOF SCOOP FOR LARGER SPILLS. DISPOSE OF AS HAZARDOUS  
WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulate

d for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.