

TURCO PRODUCTS, INC -- TURCOFORM MASK 540-R -- 8030-01-369-3186

=====
Product Identification
=====

Product ID:TURCOFORM MASK 540-R

MSDS Date:08/01/1989

FSC:8030

NIIN:01-369-3186

MSDS Number: BHGPM

=== Responsible Party ===

Company Name:TURCO PRODUCTS, INC

Address:7300 BOLSA AVE.

City:WESTMINSTER

State:CA

ZIP:92684

Info Phone Num:(714) 890-3600

Emergency Phone Num:(614) 387-6200

CAGE:0BYN5

=== Con

tractor Identification ===

Company Name:TURCO PRODUCTS, INC.

Address:7300 BOLSA AVE

Box:6200

City:WESTMINSTER

State:CA

ZIP:92684-3600

Country:US

Phone:614-387-6200

CAGE:0BYN5

Company Name:TURCO PRODUCTS, INC. DIVISON OF ELF ATOCHEM NORTH AMERICA

Address:2000 MARKET ST

Box:City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Phone:215-419-7890

CAGE:61102

=====
Composition/Information on Ingredients
=====

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS:127-1

8-4

RTECS #:KX3850000

Fraction by Wt: 65%

Other REC Limits:50 PPM A2 CARCINOGEN

OSHA PEL:100 PPM

ACGIH TLV:25PPM/100,A3 STEL;94

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 5%

Other REC Limits:STEL 400 PPM

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 10%

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:1,

3-BUTADIENE POLYMER

CAS:9003-55-8

RTECS #:WL6478000

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: SEVERE IRRITATION & POSSIBLE

TISSUE DAMAGE. SKIN: MODERATE TO SEVERE IRRITATION. INHALATION:

SEVERE IRRITATION OF RESPIRATORY TRACT, NAUSEA, HEADACHE.

INGESTION: SEVERE IRRITATION TO GASTROINTESTINAL TRACT, POSSIBLE

TISSUE DAMAGE.

Explanation of Carcinogenicity:CHLORINATED HYDROCARBONS HAVE BEEN FOUND

TO CAUSE INCREASES IN SOME TYPES OF CANCER/BENIGN TUMORS IN

MAMMALIAN SPECIES.

Effects of Overexposure:EYES: SEVERE IRRITATION & TISSUE DAMAGE. SKIN:

SEVERE IRRITATION. INHALATION: SEVERE IRRITATION OF THE RESPIRATORY

TRACT, NAUSEA, HEADACHE. INGESTION: SEVERE IRRITATION TO

GASTROINTESTINAL TRACT, TISSUE DAMAGE, HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:OVEREXPOSURE TO CHL

ORINATED

HYDROCARBONS MAY CAUSE CARDIAC IRRITABILITY & LEAD TO CARDIAC ARRHYTHMIA, AGGRAVATING ANY PREEXISTING CARDIAC DAMAGE OR DYSFUNCTION.

=====
===== First Aid Measures =====

First Aid: EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. OBTAIN MED ATT. SKIN: FLUSH AREA W/WATER. WASH W/SOAP & WATER. RINSE THOROUGHLY. OBTAIN MED ATT. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION. OBTAIN MED ATT. INGESTION: NEVER ATTEMPT TO INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point Method: SCC

Flash Point: 112F

Extinguishing Media: CO2, FOAM, WATER FOG

Fire Fighting Procedures: USE SELF-CONTAINED RESPIRATORY PROTECTION. VAPOR FROM THIS PRODUCT ARE >AIR/WILL TRAVEL ALONG THE GROUND TO COLLECT IN LOW LYING AREAS, SUCH AS SUMPS.

Unusual

Fire/Explosion Hazard: DIRECT CONTACT BETWEEN ALUMINUM/GALVANIZED METAL & CHLORINATED SOLVENTS COULD RESULT IN AN UNCONTROLLABLE CHEMICAL REACTION/EXPLOSION.

=====
===== Accidental Release Measures =====

Spill Release Procedures: CONTAIN & STOP LEAK AT SOURCE. VENTILATE AREA. EVACUATE NONESSENTIAL PERSONNEL. PUMP LIQUID, ABSORB REMAINING LIQUID & COLLECT WASHINGS TO PLACE IN DOT-APPROVED DRUMS. WASH AREA W/WATER. KEEP CONCENTRATE & WASH WATER FROM ENTERING SEWERS/WATERWAYS.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL AREA PROTECTED FROM EXPOSURE TO DIRECT SUNLIGHT, RAIN/STANDING WATER. USE CARE IN OPENING CONTAINERS TO AVOID SPURTING.

Other Precautions: DISPOSAL OF RINSE WATER: REDUCE & PRECIPITATE CHROMATES. REMOVE ORGANICS BY SKIMMING FOLLOWED BY OXIDATION/CARBON TREATMENT TO REMOVE RESIDUAL ORGANICS. DON'T LAUNDRER AT HOME.

=====
===== Exposure Co

ntrols/Personal Protection =====

Respiratory Protection: IF >TLV, A NIOSH-APPROVED SCBA, POSITIVE PRESSURE HOSE MASK/AIR LINE MASK IS ADVISED. IN AREAS OF GOOD VENTILATION, A FULL FACE MASK W/AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE USED.

Ventilation: PROVIDE SUFFICIENT MECHANICAL VENTILATION TO KEEP