View NSN Online: https://aerobasegroup.ae/nsn/6850-01-263-8433

AMERICAN GAS AND CHEMICAL COMPANY., LTD. -- FLAW-FINDER AG-3D-FS PENETRANT - 6850-01-263-8433

Product ID:FLAW-FINDER AG-3D-FS PENETRANT MSDS Date:01/03/1989 FSC:6850 NIIN:01-263-8433 MSDS Number: BHKWJ === Responsible Party === Company Name: AMERICAN GAS AND CHEMICAL COMPANY., LTD. Address:220 PEGASUS AVENUE **City:NORTHVALE** State:NJ ZIP:07647-1904 Country:US Info Ph one Num:201-767-7300 Emergency Phone Num:201-767-7300 Preparer's Name: GEORGE KOSEL, CHIEF CHEM CAGE:03530 === Contractor Identification === Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD Address:220 PEGASUS AVENUE, City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Phone:201-767-7300 CAGE:03530

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III) CAS:117-81-7 RTECS #:TI0350000 Fraction by Wt: 60.0% OSHA PEL:5 MG/M3/10 STEL ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:TRIPHENYL PHOSPHATE CAS:115-86-6 RTECS #:TC8400000 Fraction by Wt: 1.0% OSHA PEL:3 MG/M3 ACGIH TLV:3 MG/M3; 9192

Ingred Name:PER MANUFACTURER'S MSDS,ITEM CONTAINS NO OTHER HAZARDOUS INGREDIENTS ACCORDING TO THE PROVISIONS GIVEN IN 29CFR1910.2000 RTECS #:99999992Z Fraction by Wt: BALANCE

LD50 LC50 Mixture:NONE ESTABLISHED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: CAUSES IRRITATION OF EYES, SKIN, RESPIRATORY TRACT; INGESTION MAY CAUSE NAUSEA, VOMITING, ETC.. INGESTION OF SMALL QUANTITIES IS USUALLY NON-FATAL UNLESS ASPIRATION OCCURS. ASPIRATION MAY LEAD TO CHEMICAL PNEUMONITIS. Explanation of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE LISTED AS AN ANIMAL CARCINOGEN, IT IS NOT LISTED AS HUMAN CARCINOGEN, PER MFR MSDS INFORMATION. Effects of Overexposure: INHALATION: DUE TO ITS LOW VOLATILITY, EXPOSURE TO THIS MATERIAL UNDER AMBIENT CONDITIONS IS NOT EXPECTED TO PRODUCE ADVERSE HEALTH EFFECTS FOLLOWING NORMAL WORKPLACE EXPOSURE: SKIN: CAN CAUSE SLIGHT IRRITATION; EYES: MAY CAUSE IRRITATION; INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. Medical Cond Aggravated by Exposure:NONE CURRENTLY KNOWN.

First Aid:INHALATION: REMOVE TO FRESH AIR: SEEK MEDICAL HELP.IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. GIVE OXYGEN IF NEEDED; SKIN AND EYES: FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES. SEEK MEDICAL HELP IF IRRITATION PERSISTS; INGESTION: DO NOT INDUCE VOMITING. IMMEDIATELY CALL A PHYSICIAN.

Flash Point:NONE (AEROSOL)

Exting

uishing Media:REGULAR FOAM, WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPOR OR FUMES.

Unusual Fire/Explosion Hazard: AEROSOL CONTAINERS MAY BURST/EXPLODE IN HEAT OF FIRE.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION: REMOVE IGNITION SOURCES: RECOVER

FREE LIQUID; USE SUITABLE INERT ABSORBENT SUCH AS SAND, CLAY, ETC. TO ABSORB LIQUID. KEEP MATERIAL OUT OF SEWERS/WATER WAYS.LG SPILLS MAY BE P ICKED UP BY VACUUM PUMPS, SHOVELS & PLACEIN DRUMS.

Handling and Storage Precautions:STORE IN A COOL DRY PLACE BELOW 120F. DO NOT PUNCTURE OR DAMAGE CONTAINERS. DO NOT STORE OR HANDLE NEAR HEAT,SPARKS OR OXIDANTS.KEEP PLAINLY LABELED.

Other Precautions:DO NOT PRESSURIZE, C

UT, WELD, BRAZE, SOLDER, DRILL,

GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION, THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.DO NOT ATTEMT TO CLE AN SINCE RESIDUE IS DIFFICULT TO REMOVE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF NEEDED. Ventilation:GOOD,GENRAL VENTILATION IS SUFFICIENT. Protective Gloves:NON ABSORBENT GLOVES Eye Protection :SAFETY GLASSES
Other Protective Equipment:USE CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING IF NEEDED TO AVOID CONTAMINATING REGULAR CLOTHING.EYE-WASH FAC
Work Hygienic Practices:ADHERE TO GENERAL INDUSTRIAL HYGIEN PRACTICE AT THE WORKPLACE.
Supplemental Safety and Health
NSN IS FOR PENETRANTS OF TYPE I, METHOD C, LEVEL 3 OF MIL-I-25135, REV E. IN ACCORDANCE WITH QPL-25135-15, FLUORO-FINDER AG-3A-FW, AND FLAW-FINDER AG-3D-FS PENTRANTS ARE TYPE I, METHOD C AND LEVEL 3

Ρ

RODUCTS. THIS ENTRY DESCRIBES FLUORO-FINDER AG-3D-FS PENETRANT. SEE PNI B,THIS NSN, FOR FLAW-FINDER AG-3A-FW PENETRANT.

HCC:V1 Boiling Pt:B.P. Text:N/R(AEROSOL Vapor Pres:1.0(AIR=1 Spec Gravity:0.98 (BULK) Evaporation Rate & amp; Reference:0.1 (N BUAC=1) (BULK) Solubility in Water:NEGLIGIBLE Appearance and Odor:BULK PRODUCT: YELLOW-GREEN LIQUID;MILD ODOR Percent Volatiles by Volume:>95%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENT. Stability Condition to Avoid:EXTREME HEAT Hazardous Decomposition Products:BURNING CAN PRODUCE CARBON DIOXIDE AND/OR CARBON MONOXIDE.

Waste Disposal Methods:WASTE PRODUCT SHOULD BE INCINERATED OR DISPOSED OF IN AN APPROVED DISPOSAL SITE OR FACILITY.CAN BE RECLAIMED AND RECYCLED.ASSURE CONFORMITY WITH ALL APPL ICABLE LOCAL,STATE AND FEDERAL DISPOSAL REGULAT IONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the s uitability of this information to their particular situation.