View NSN Online: https://aerobasegroup.ae/nsn/6850-01-268-6695

AMERICAN GAS AND CHEMICAL COMPANY., LTD. -- FLAW-FINDER AG-4B-FS PENETRANT - 6850-01-268-6695

Product ID:FLAW-FINDER AG-4B-FS PENETRANT MSDS Date:01/03/1989 FSC:6850 NIIN:01-268-6695 MSDS Number: BHKZN === Responsible Party === Company Name: AMERICAN GAS AND CHEMICAL COMPANY., LTD. Address:220 PEGASUS AVENUE City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Info Ph one Num:201-767-7300 Emergency Phone Num:201-767-7300 Preparer's Name: GEORGE KOSEL, CHIEF CHEM CAGE:03530 === Contractor Identification === Company Name: AMERICAN GAS AND CHEMICAL COMPANY, LTD Address:220 PEGASUS AVENUE, City:NORTHVALE State:NJ ZIP:07647-1904 Country:US Phone:201-767-7300 CAGE:03530

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III) CAS:117-81-7 RTECS #:TI0350000 Fraction by Wt: 60.0% OSHA PEL:5 MG/M3/10 STEL ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:TRIPHENYL PHOSPHATE CAS:115-86-6 RTECS #:TC8400000 Fraction by Wt: 1.0% OSHA PEL:3 MG/M3 ACGIH TLV:3 MG/M3; 9192

Ingred Name:PER MANUFACTURER'S MSDS,ITEM CONTAINS NO OTHER HAZARDOUS INGREDIENTS ACCORDING TO THE PROVISIONS GIVEN IN 29CFR1910.2000 RTECS #:99999992Z Fraction by Wt: BALANCE

Routes of Entry: Inhalation:NO Ski n:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: CAUSES IRRITATION OF EYES, SKIN, RESPIRATORY TRACT; INGESTION MAY CAUSE NAUSEA, VOMITING,ETC...INGESTION OF SMALL QUANTITIES IS USUALLY NON-FATAL UNLESS ASPIRATION OCCURS. ASPIRATION MAY LEAD T O CHEMICAL PNEUMONITIS. Explanation of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE IS LISTED AS AN ANIMAL CARCINOGEN, IT IS NOT LISTED AS HUMAN CARCINOGEN, PER MFR MSDS I

NFO.

Effects of Overexposure:INHALATION: DUE TO ITS LOW VOLATILITY, EXPOSURE TO THIS MATERIAL UNDER AMBIENT CONDITIONS IS NOT EXPECTED TO PRODUCE ADVERSE HEALTH EFFECTS FOLLOWING NORMAL WORKPLACE EXPOSURE; SKIN: CAN CAUSE SLIGHT IRRITATION; EYES: MAY CAUSE IRRITATION;INGESTION:CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:NONE CURRENTLY KNOWN.

Fi

rst Aid:INHALATION: REMOVE TO FRESH AIR: SEEK MEDICAL HELP.IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. GIVE OXYGEN IF NEEDED; SKIN AND EYES: FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES. SEEK MEDICAL HELP IF IRRITATION PERSISTS; INGESTION: DO NOT INDUCE VOMITING. IMMEDIATELY CALL A PHYSICIAN.

Flash Point Method:PMCC Flash Point:252F/122C Extinguishing Media:REGULAR FOAM,WATER FOG,CARBON DIOXIDE,DRY CHEMICAL. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPOR OR FUMES. Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST/EXPLODE IN HEAT OF FIRE.

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:REMOVE IGNITION SOURCES:RECOVER FREE LIQUID;USE SUITABLE INERT ABSORBENT SUCH AS

SAND,CLAY,ETC.TO ABSORB LIQUID.KEEP MATERIAL OUT OF SEWERS/WATER WAYS.LG SPILLS MAY BE P ICKED UP BY VACUUM PUMPS,SHOVELS & PLACE IN DRUMS.

Handling and Storage Precautions:STORE IN A COOL DRY PLACE BELOW 120F.DO NOT PUNCTURE OR INCINERATE CONTAINERS.DO NOT STORE OR HANDLE NEAR HEAT,SPARKS OR OXIDANTS.KEEP PLAINLY LABELED
Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXP
OSE SUCH CONTAINERS TO HEAT, FLAME,SPARKS OR OTHER

SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.DO NOT ATTEMPT TO CLE AN SINCE RESIDUE IS DIFFICULT TO REMOVE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF NEEDED. Ventilation:GOOD,GENERAL VENTILATION IS SUFFICIENT. Protective Gloves:NON ABSORBENT GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:USE C HEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING, IF NEEDED, TO AVOID CONTAMINATING REGULAR CLOTHING.EYE-WASH FAC
Work Hygienic Practices: ADHERE TO GENERAL INDUSTRIAL HYGIEN PRACTICE AT THE WORKPLACE.
Supplemental Safety and Health
NSN IS FOR TYPE I, METHOD B, LEVEL 4 PENETRANTS OF MIL-I-25135, REV E; PER QPL-25135-15, AG-4B-FS PENETRANT QUALIFIES THE REQUIREMENTS FOR TYPE I, METHOD B, LEVEL 4 MATERIAL.

Н

CC:T6 Boiling Pt:B.P. Text:440F IBP Vapor Pres:1.0(AIR=1 Spec Gravity:0.98 Evaporation Rate & amp; Reference:95%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENT. Stability Condition to Avoid:EXTREME HEAT Hazardous Decomposition Products:BURNING CAN PRODUCE CARBON DIOXIDE AND/OR CARBON MONOXIDE.

Waste Disposal Methods:WASTE PRODUCT SHOULD BE INCINERATED OR DISPOSED OF IN AN APPROVED DISPOSAL SITE OR FACILITY.CAN BE RECLAIMED AND RECYCLED.ASSURE CONFORMITY WITH ALL APPLICABLE LOCAL,STATE AND

FEDERAL DISPOSAL REGULAT IONS.DO NOT INCINERATE EMPTY/PARTIALLY FILLED CANS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this info rmation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.