

THERMOSET PLASTICS, INC. -- 600 RESIN -- 8030-00-086-1506

=====
Product Identification
=====

Product ID:600 RESIN

MSDS Date:12/07/1989

FSC:8030

NIIN:00-086-1506

MSDS Number: BHMDL

=== Responsible Party ===

Company Name:THERMOSET PLASTICS, INC.

Address:6101 EAST 65TH STREET

Box:20902

City:INDIANAPOLIS

State:IN

ZIP:46220-0902

Country:US

Info Phone Num:DAY 317-252-8430

Emergency Phone Num:317-259-41

61, NIGHT 317-769-3259

Preparer's Name:RICHARD L. WHEELER

CAGE:IO099

=== Contractor Identification ===

Company Name:THERMO PLASTICS, INC.

Address:5101 EAST 65TH STREET

Box:20902

City:INDIANAPOLIS

State:IN

ZIP:46220-0902

Country:US

Phone:317-259-4161(DAY) 769-3259(NIGHT)

CAGE:22156

Company Name:THERMOSET PLASTICS INC

Address:5101 EAST 65TH STREET

Box:20902

City:INDIANAPOLIS

State:IN

ZIP:46220-0902

Country:US

Phone:317-252-8430

CAGE:IO099

=====
Composition/Information on Ingredients
=====

=====

Ingred Name: DIGLYCIDYL ETHER BISPHENOL A RESIN
CAS: 25068-38-6
RTECS #: KC2100000
ACGIH TLV: NONE ESTABLISHED

===== Hazards Identification =====

Routes of Entry: Inhalation: NO Skin: YES Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: SKIN: CAUTION! MAY CAUSE SKIN
IRRITATION. PREVENT PROLONGED OR FREQUENT SKIN CONTACT. EYE:
WARNING! CAUSES EYE IRRITATION. AVOID CONTACT WITH EYES.

Effects of

Overexposure: SKIN: IRRITATION. EYES: IRRITATION.
INHALATION: NOT LIKELY A PROBLEM. INGESTION: UNKNOWN.
Medical Cond Aggravated by Exposure: NONE KNOWN

===== First Aid Measures =====

First Aid: SKIN: WIPE OFF EXCESS CONTAMINATION. REMOVE ANY CONTAMINATED
CLOTHING AND WASH WITH SOAP AND WATER. EYE: IMMEDIATELY FLUSH EYE
WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL
ATTENTION. INHALATION: NOT LIKELY A PROBLEM. INGESTION

: IN GENERAL

NO TREATMENT IS NECESSARY UNLESS LARGE QUANTITIES OF PRODUCT
ARE INGESTED. HOWEVER, GET MEDICAL ADVICE.

===== Fire Fighting Measures =====

Flash Point Method: PMCC

Flash Point: 480 F / 298C

Lower Limits: ND

Upper Limits: ND

Extinguishing Media: WATER FOG, FOAM, CO2, AND DRY CHEMICALS.

Fire Fighting Procedures: NO SPECIAL PROCEDURES- AVOID BREATHING

SMOKE. SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTH SHOULD
BE WORN WHEN FIGHTING

LARGE FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard: NO UNUSUAL HAZARDS KNOWN TO THERMOSET
PLASTICS.

===== Accidental Release Measures =====

Spill Release Procedures: SOAK UP WITH ABSORBENT OR PAPER TOWELS AND
DISPOSE OF PROPERLY. SHUT OFF SOURCE OF LEAK, IF SAFE TO DO SO. DIKE
AND CONTAIN. SOAK UP RESIDUE WITH ABSORBENTS SUCH AS CLAY, SAND,
ETC. DISPOSE OF PROPERLY. FLUSH AREA W/ALCOHOL SOLVENT, OBSERVING
FIRE HAZARD.

=====

Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. AVOID EXCESSIVE HEAT OR COLD. AVOID MOISTURE CONTAMINATION.

===== Exposure Controls/Personal Protection =====

Ventilation:ROOM EXHAUST ACCEPTABLE.

Protective Gloves:RUBBER OR PLASTIC.

Eye Protection:SAFETY GLASSES W/SIDE SHIELD,CHEM GOGGLE

Other Protective Equipment:APRON IF NEEDED.SAFETY SHOWER AND EYE WASH STATION SHOULD BE AVAILABLE IN THE WORK AREA.

Work Hygi

enic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE AND WASH CONTAMINATEDCLOTHING BEFORE REUSE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>500 F

Vapor Pres:NEG

Vapor Density:NA

Spec Gravity:1.16

Evaporation Rate & Reference:NA

Solubility in Water:NEGLIGIBLE (