

PRATT & LAMBERT, INC. -- LAC SPRAY CHEM RESIST BLK 17038 -- 8010-00-290-6158

=====
Product Identification
=====

Product ID:LAC SPRAY CHEM RESIST BLK 17038

MSDS Date:12/15/1988

FSC:8010

NIIN:00-290-6158

MSDS Number: BHMKK

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Prep

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingredient Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PP
M; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/30

OSTEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC. ORGANIC CMPD 5.7 LB/GAL LESS WATER & NPRS* 684 G/L
LESS WATER VOC. 34.0 LB/GAL SOLIDS 4080 G/L SOLIDS CALCU
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ASPIRATION OF MATL INTO LUNG MAY CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. HI CONC MAY CAUSE CNS
DEPRESSION.OVEREXPOSURE
TO TOLUENE MAY CAUSE LIVER
DAMAGE.OVEREXPOSURE TO SOLVENTS W/PERMANENT BRA IN & NERVOUS SYSTEM
DAMAGE. INTENTIONALMISUSE MAY BE HARMFUL OR FATAL.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS
A POTENTIAL CARCIN- OGEN BY THE NATIONAL TOXICOLOGY PROGRAM.
Effects of Overexposure:EYES: MAY CAUSE EYE IRRITATION. SKIN: MAY CAUSE
DEFATTING AND IRRITATION TO THE SKIN. INHALATION: MAY CAUSE NOSE OR
THROAT IRRITATION. AND INGESTION: MAY CAUSE GASTROINTESTINAL

IRRITATION, NAUSEA AND VOMITING.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING LIDS 15
MINS. GET MEDICAL ATTN.SKIN: IMMED FLUSH CONTAM AREA WITH LARGE
AMTS OF WATER WHILE REMOVING CLOTHES. GET MED ATTN. INHALE: REMOVE
TO FRESH AI R IMMED, CPR IF NEEDED, KEEP PERSON WARMQUIET, GET MED
ATTN IMMED. INGESTION: DO NOT INDUCE VOMITING, CALL HOSPITAL OR
PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:20F/-6.67C
Extinguishing Media:CLASS B FIRE EXTINGUISHERS TO EXTINGUISH FLAMMABLE
LIQUID FIRES POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE
WATER TO COOL EXPOSED CONTAINERS TOPREVENT PRESSURE BUILD-UP &
POSSIBLE EXPLOSION. FOG NOZZLE PREFERRED WITH WATER.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE HEALTH HAZARD.

OBTAIN MEDICAL ATTENTION. KEEP CONTAINER
CLOSED. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS, FLAMES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE &
CONTAIN SPILL W/INERT MATL. USE ONLY NON-SPARKING TOOLS. PREVENT
CONTAMINATION OF SEWERS, STREAMS & GROUND WATER W/SPILLED MATL OR
USED ABSORBENT. WEAR RESP. EYE, HAND & BODY PROTECTION
APPROPRIATEFOR SPILL.

===== Handling and
Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 F. STORE LARGE
QUANITITES INCOMPLIANCE W OSHA 29CFR1910.106. CLOSE CONTAINER
AFTER EACH USE. NEVER USE PRESSURE TO EMPTY.

Other Precautions:DO NOT TAKE INTERNALLY. EMPTY CONTAINERS MUST NOT BE
WASHED OR RE-USED FOR ANY PURPOSE. DO NOT WELD, BRAZE OR CUT ON
EMPTY CONTAINER. DRUM IS NOT A PRESSURE VESSEL. CONTAINERS SHOULD
BE GROUNDED AN D/OR BONDED TO THE RECEIVING CONTAINERS.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED AREAS USE A NIOSH APPROVED
CHEMICAL CARTRIDGE RESPIRATOR. AND FOR SPRAYING USE A MECHANICAL
PREFILTER. IN CONFINED AREAS USE A NIOSH/MSHA APPROVEDAIR SUPPLIED
RESPIRATOR.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST IN SUFFICIENT VOLUME/PATTERN
TO MAINTAIN BELOW THE LOWEST EXPOSURE LIMITS.

Protective Gloves:IMPERMEABLE GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:

EYE WASH FACILITY AND/OR SAFETY SHOWER.

Work Hygienic Practices:NK.

Supplemental Safety and Health
NK.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175F-302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:83

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to A

void:AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON
DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND/OR
FLAMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL, STATE & LOCAL
LAW INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE

CLOSED CONTAINERS. PLACE DIKING MATERIAL IN COVERED METAL
CONTAINERS FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.