

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS GREEN 14064 ID742412 -- 8010-00-298-2295  
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS GREEN 14064 ID742412

MSDS Date:03/23/1988

FSC:8010

NIIN:00-298-2295

MSDS Number: BHMNM

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:31

6-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:MINERAL SPI

RITS  
(VAPOR PRESSURE 2 MMHG @ 20C)

CAS:64475-85-0  
RTECS #:PY8240000  
OSHA PEL:500 PPM 2950 MG/CU.M  
ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GAL LESS WATER & NPRS\* 480 G/L  
LESS WATER VOC. 10.6 LB/GAL SOLIDS 1272 G/L SOLIDS CALCU  
RTECS #:9999999VO

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:Y  
ES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PROLONGED/REPEATED OCCUP OVEREXPOSURE  
TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.  
INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATION & INHALING THE  
CONTENTS MAY BE HARMFUL OR FATAL  
Explanation of Carcinogenicity:NONE CURRENTLY KNOWN  
Effects of Overexposure:SWALLOW: GASTROINTESTINAL IRRI, NAUSEA, VOMIT,  
ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FA  
TAL. INHAL:  
NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERV SYS DEPRESSION  
CHAR HEADACHE, DIZZ, NA USEA & CONFUSION. EYE: IRRI. SKIN: DEFATTNG  
AND IRRITATION OF THE SKIN. INHAL OF CAN CAUSE ASPHYXIATION OR  
ANESTHETIC.

=====  
===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL  
CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH  
AIR IMMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUI

ET. GET MED

ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS,  
FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES.  
WASH AFFECT AREA W/SOAP & WTR. OBTAIN MED ATTN. IRRI PERSISTS.

=====  
Fire Fighting Measures  
=====

Flash Point:> 102 F/39 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY  
CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRE. POLYMER FOAM  
PREFERR

Fire Fighting Procedures:SELF CONTAIN  
N BREATH APPARATUS. WTR MAY BE  
INEFFECT, USED TO COOL TO PREVENT PRESSURE  
BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZLES  
PREFERR

Unusual Fire/Explosion Hazard:EMERG COND, OVEREXP TO DECOMP MAY CAUSE  
HEALTH HAZARD. SYMP MAY NOT BE IMMED APPARENT. OBTAIN MED ATTN.  
WARNING! FLAMMABLE. CLOSE CONT. ISOLATE FROM HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNITE SOURCES.

DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQ TO COVER METAL  
CONTAIN FOR RECOVERY/DISPOSAL. USE NON-SPARK TOOL. PREVENT CONTAM  
OF SEWERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED  
ABSORB

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE  
LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 DO NOT TAKE  
INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:KEEP AWAY  
FROM CHILDREN. DO NOT BREATHE SANDING DUST.  
WASH HANDS & FACE THOROUGHLY BEFORE EATING/DRINKING. EMPTY CONT  
MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONT GROUNDED/BONDED  
TO RECEIVING CO NT. DO NOT WELD/BRAZE/CUT EMPTY CONT.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:GEN EXP TO ORGANIC CHEM MAY NOT REQUIRE RESPIR  
PROTECT IF WELL VENT AREA. RESTRICTED VENT AREA NIOSH APPROVED CHEM  
CARTRIDGE RESPIR MAY BE REQUIRED. SPRAYNG:

MECH PREFILTER MAY ALSO  
BE REQUIRED. CONFIDENTIAL: NIOSH APPROVED AIR SUPPLIED RESPIRATOR  
Ventilation: GENERAL DILUTION & LOCAL EXHAUST VENT SUFFICIENT VOLUME/PATTERN  
KEEP CONCENTRATION HAZARDOUS INGREDIENTS BELOW THE LOWEST EXPOSURE LIMIT  
Protective Gloves: PROLONGED USE, SOLVENT IMPERMEABLE GLOVE  
Eye Protection: SAFETY GLASSES/CHEM GOGGLES/FACE SHIELDS  
Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT. NOT  
LIKELY TO BE NEEDED SEE OSHA STANDARD FOR LEAD.

Supplemental Safety and Health

THIS PRODUCT,

IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS  
WASTE BASED ON ITS IGNITABILITY CHARACTER. THIS PRODUCT CONTAINS LEAD,  
WHICH, IF PRESENT IN WASTE AT 5.0 MG/L OR MORE AFTER BEING EXTRACTED,  
IS CONSIDERED EP TOXIC, AND THEREFORE A HAZARDOUS WASTE UNDER  
RCRA REGULATIONS. HAZARD WASTE NO. D008

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 280-388 F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by

Volume: 61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: NORMALLY STABLE. AVOID EXCESSIVE HEAT &  
SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDE WHEN HEATED BY  
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE. OXIDES  
OF LEAD-GENERATED

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

=====

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF ACCORD TO FEDERAL, STATE & LOCAL LAWS. INCINERATE  
ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE  
PRECAUTIONS FOR FLAMMABLE DISPOSAL. CONTAMINANTS ABSORBED IN HAZARDOUS  
WASTE LANDFILL. IN ACCORD WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.