

NORRIS PAINT COMPANY -- NORRIS DREAMHOUSE LTX,FLT WALL PNT, ID WDHTI  
8010-00-515-2238

===== Product Identification =====

Product ID:NORRIS DREAMHOUSE LTX,FLT WALL PNT, ID WDHTI

MSDS Date:06/05/1987

FSC:8010

NIIN:00-515-2238

MSDS Number: BHMQL

==== Responsible Party ===

Company Name:NORRIS PAINT COMPANY

Address:1675 COMMERCIAL STREET N.E.

City:SALEM

State:OR

ZIP:97303

Country:US

Info Phone Num:503-

364-2277

Emergency Phone Num:503-364-2277

Preparer's Name:P.H. PAYNE

CAGE:JO883

==== Contractor Identification ===

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

Company Name:NORRIS PAINT COMPANY

Box:2023

CAGE:JO883

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2%

OSHA PE

L:C 50 PPM  
ACGIH TLV:C 50 PPM,VAPOR; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 14%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Fraction by Wt: 9%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:CLAY  
CAS:1335-30-4  
Fraction by Wt: 18%  
ACGIH TLV:10 PPM 15 MG/M3

Ingred Name:SILICA, AMORPHOUS, DUST  
CAS:112945-  
52-5  
RTECS #:VV7310000  
Fraction by Wt: 5%  
OSHA PEL:6 MG/M3  
ACGIH TLV:10 MG/M3; 8990

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Effects of Overexposure:EYE: IRRITATION, REDNESS, TEARING, BLURRED  
VISION. SKIN: DRY AND DEFAT LEADING TO  
IRRITATION & DERMATITIS. INGESTION: NAUSEA,  
VOMITING, DIARRHEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH

CLEAR WATER UNTIL IRRITATION SUBSIDES.

CONSULT PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING, WASH SKIN WITH SOAP & WARM WATER. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NA

Fire Fighting Procedures:NA

Unusual Fire/Explosion Hazard:NA

===== Accidental Release Measures =====

Spill Release Procedures:

ISOLATE THE AREA, RECOVER FREE LIQUID WITH AN ABSORBENT (SAND,EARTH,SAWDUST,ETC.) KEEP OUT OF SEWERS BY DIKING, IMPOUNDING.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:KEEP FROM FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NA

Ventilation:NA

Protective Gloves:IF NEEDED TO AVOID SKIN CONTACT

Eye Protection:SP

LASH GOGGLES

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:108F/82C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

VINYL ACETATE MONOMER; ACRYLIC MONOMER

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE

CONFORMITY WITH APPLICABLE DISPOSAL  
REGULATIONS FOR BOTH SPILLED PRODUCT AND ABSORBED MATL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to ver  
ify and  
assume responsibility for the suitability of this information to their  
particular situation.