

PRATT & LAMBERT INC -- LACQUER CAMOUFLAGE GREEN 34300 ID 787451 -- 8010-00-524-9766
===== Product Identification =====

Product ID:LACQUER CAMOUFLAGE GREEN 34300 ID 787451

MSDS Date:08/21/1990

FSC:8010

NIIN:00-524-9766

MSDS Number: BHMQP

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316

-733-1361

Preparer's Name:W. A. ELLISON

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fract

ion by Wt: 20%
Other REC Limits:LFL 2.0/UFL 11.0
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:LFL 3.0/UFL 13.0
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fr
action by Wt: 5%
Other REC Limits:LFL 1.0/UFL 11.0
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
Other REC Limits:LFL 1.7/UFL 7.1
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qt

y:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:LFL 1.0/UFL 7.0

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:W

W2710000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: < 5%

Other REC Limits:LFL 1.4/UFL 11.2

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC 5.02 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY

REACTIVE MATERIALS 602 G/L LESS WATER

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTINAL IRRIT & CHEMICAL PNEUMONITIS. INHALATION MAY CAUSE NOSE/THROAT IRRITATION. EYE & SKIN IRRITANT; HARMFUL AMTS CAN CAUSE SKIN DEFATTING. OTHER EFFECTS: LUNG DISEASE , DAMAGE TO LIVER, KIDNEYS, BLOOD, PREEXISTING RESPIRATORY CONDITIONS, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE & DEATH.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS CRYSTALLINE SILICA, WHICH IS LISTED AS A POTENTIAL CARCINOGEN BY THE IARC.

Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, VOMITING, CONFUSION & SEVERE IRRITATION REACTION IF PRODUCT IS SWALLOWED, INHALED, ABSORBED THROUGH SKIN, OR GETS INTO EYES.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY COND MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA. REPORTS ASSOCIATED
PROLONGED/REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====
First Aid Measures
=====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER IMMED. INHALATION: REMOVE TO FRESH AIR IMMED. IF BREATHING STOPPED, GIVE CPR & KEEP WARM. EYE: FLUSH W/LRG AMTS OF WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS CONTINUOUSLY. SKIN:IMMEDIATELY FLUSH CONTAMINATED AREA W/LRG AMTS OF WATER. REMOVE CONTAMINATED CLOTHES AS WATER IS APPLIED. GET MEDICAL ATTN IMMED FOR ANY OF THESE CONDITIONS.

=====
Fire Fighting Measures
=====

Flash Point:40F/4C
Lower Limits:SEE INGRED
Upper Limits:SEE INGRED
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT P

RESSURE BUILDUP & POSSIBLE

AUTO-IGNITE EXPLOS. FOG NOZZLES PREFERRED W/WATER.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO COVERED ME

TAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARKING TOOLS. PREVENT CONTAMINATION OF S EWERS, STREAMS, & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:EMPTY CONTAINERS SHOULD NOT BE WASHED OR REUSED FOR ANY PURPOSE AND SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EM

PTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DISPO SE AS HAZARDOUS WASTE, IGNITABLE, D001.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONFINED AREAS USE A NIOSH/ MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:DILUTION & LOCAL EXHAUST VENTILATION RECOMMENDED TO CONTROL

CONCENTRATE OF HAZARDOUS INGREDIENTS.

Protective Gloves:WEAR SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES, SIDE/FACE SHIELD

Work Hygienic Practices:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE & KEEP AWAY FROM CHILDREN.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180 TO 246F

Vapor Density:> THAN AIR

Spec Gravity:1.1

Evaporation Rate & Reference:SLOWER THAN ETHER

Pe

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.

Hazardous Decomposition Products: BURNING, HEAT BY WELDING OR CUTTING,
WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF
NITROGEN.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND
FLAME.

=====
===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS.
INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS. OBSERVE PRECAUTIONS FOR DISP OF FLAMMABLE MATERIALS.
CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense.

The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.