

CONSTRUCTION ADHIVES COMPANY, INC. -- ADHESIVE GROUT TYPE II PART A AND B --
8040-00-726-3567

===== Product Identification =====

Product ID:ADHESIVE GROUT TYPE II PART A AND B

MSDS Date:01/01/1987

FSC:8040

NIIN:00-726-3567

MSDS Number: BHMTX

=== Responsible Party ===

Company Name:CONSTRUCTION ADHIVES COMPANY, INC.

Address:969 MARKET STREET

City:PATERSON

State:NJ

ZIP:07513

Country:US

Info Phone

Num:201-742-8333

Emergency Phone Num:201-444-2464 OR 201-756-3688

CAGE:CONST

=== Contractor Identification ===

Company Name:CONSTRUCTION ADHIVES COMPANY, INC.

Address:969 MARKET STREET

City:PATERSON

State:NJ

ZIP:07513

Country:US

Phone:201-742-8333

CAGE:CONST

===== Composition/Information on Ingredients =====

Ingred Name:BISPHENOL A EPXOY RESIN

CAS:25068-38-6

RTECS #:SL6310000

Ingred Name:TEPA TETRAETHYLENE PENTAMINE

CAS:112-57-2

RTECS #:KH8580000

Ingred Name:ALIPHATIC AMIN

ES

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE ALLERGIC REACTION ON
SENSITIVE SKIN AND EYES
Effects of Overexposure:ITCHINESS AND RASH
Medical Cond Aggravated by Exposure:NOT KNOWN

=====
First Aid Measures
=====

First Aid:WASH WITH SOAP AND WATER THOROUGHLY AND APPLY SALVE AS
RECOMMENDED BY PHYSICIAN

=====
Fire Fighting Measures
=====

Flash Point Method:CC
Flash Point:490 F/254.44 C
Extinguishing Media:WATER SPRAY, CO2 OR DRY CHEMICAL
Fire Fighting Procedures:WEAR ORGANIC VAPOR MASK. FUMES MAY BE
IRRITATING
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:SWEEP UP WITH SAND OR ABSORBANT

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE IN EXCESSIVE HEAT OR MIX
AT ELEVATED TEMPERATURES (70 DEG F IS NORMAL)
Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NORMALLY BUT AN ORGANIC VAPOR MASK COULD BE
USED IN A CONFINED AREA
Ventilation:LOCAL EXHAUST IS NORMAL
GENERAL IN A CONFINED AREA
Protective Gloves:WEAR RUBBER GLOVES
Eye Protection:WEAR SAFETY GLASSES
Other Protective Equipment:N

ONE

Work Hygienic Practices:WORK SAFELY AS DESCRIBED ABOVE

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:210 DEG C

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.17 & 0.97

Evaporation Rate & Reference:NA

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR PART A AND B WILL SOLIDIFY WHEN MIXED-MILD
ODOR

===== Stability and Reactivity Data =====

ta =====

Stability Indicator/Materials to Avoid:YES

NK

Stability Condition to Avoid:ELEVATED TEMPERATURES

Hazardous Decomposition Products:TOXIC FUMES MAY BE EVOLVED WHEN
INVOLVED IN FIRE

===== Disposal Considerations =====

Waste Disposal Methods:COMBINE BOTH PARTS TO CAUSE SOLID MASS RESULTING
SOLID IS INERT & MAY BE DISPOSED OF IN A NORMAL MANNER

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.