View NSN Online: https://aerobasegroup.ae/nsn/8010-00-753-4549

Product ID: ENAMEL ALKYD GLOSS GRN 14050 ID742404 MSDS Date:03/23/1988 FSC:8010 NIIN:00-753-4549 **MSDS Number: BHMTZ** === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name:W.A. ELLISON С AGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OS HA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC. ORGANIC CMPD 4.1 LB/GAL LESS WATER & NPRS* 492 G/L LESS WATER VOC. 10.7 LB/GAL SOLIDS 1284 G/L SOLIDS CALCU RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:REPORTS HAVE ASSOC PROLONG/REPEATED OCCUP OVEREXPOSURE TO SOLVENTS W/PERMANEN
T BRAIN & NERVOUS SYSTEM
DAMAGE. INTENTIONAL MISUSE BY DELIBERTELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
Explanation of Carcinogenicity:MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.
Effects of Overexposure:SWALLOW: GASTROINTESTINAL IRRI, NAUSEA, VOMIT, ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FATAL. INHAL: NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERVOUS SYS DEPRESSION CHAR HEADACHE, DIZZ, NAUSEA & CONFUSION.
EYE: IRRI.

SKIN: DEFATTNG AND IRRITATION OF THE SKIN

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH AIR IMMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUIET. GET MED ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS, FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECT AREA WITH SOAP & WATER. OBTAIN MED ATTN. IF IRRI

PERSISTS.

Flash Point Method:SCC Flash Point:> 102 F/38.89 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) EXTING FLAMM LIQ FIRES. POLYMER FOAM PERFERRED

Fire Fighting Procedures:SELF CONTAIN BREATH APPARATUS. WTR MAY BE INEFFECT, USED TO COOL TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM HEAT. IF WTR USED, FOG NOZZ LES

PREFERR

Unusual Fire/Explosion Hazard:EMERG COND OVEREXPOSURE DECOMP PRODUCTS CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BEIMMD APPARENT. OBTAIN MED ATTN. KEEP CONT TIGHTLY CLOSED. ISOLATE FROM HEAT, ETC

Spill Release Procedures: KEEP SPECTATORS AWAY. ELIM ALL IGNITION SOURCES. DIKE/CONTAIN W/INERT MATERIAL. TRANSFER LIQ TO COVERED METAL CONTAIN FOR RECOVERY/DISPOSAL. USE NON-SPARK TOOLS. PREVENT CONTAM

OF SEWERS, STREAMS GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORB

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LRG QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. WASH HANDS & FACE THOROUGHLY BEFORE EATING OR DRINKING. EMPTY CONT MUST NOT BE WASHED & RE-U

SED FOR ANY PURPOSE. CONT SHOULD BE GROUDED/BONDED TO RECEIVING CONT. DO NOT WELD, BRAZE, ETC.

Respiratory Protection: GENERAL EXPOSURE TO ORGANIC CHEM MAY NOT REQUIRE THE USE OF RESPIR PROTECTION IFWELL VENT AREA. RESTRICTED VENT: NIOSH APPROVED CHEM CARTRIDGE RESPIR MAY BE REQUIRED. UNDER SPRAYING: MECH PREFILTER. C ONFINED AREA: AIR SUPPLIED RESPIRATOR Ventilation: GEN DILUTION & LOCAL EXHAUST VENT SUFFICIENT VOLUME/PATTERN

KEEP CONCEN HAZARD INGRED BELOW THE LOWEST EXPOSURE LIMIT Protective Gloves: PROLONGED USE, SOLVENT IMPERMEABLE GLOVE Eye Protection: WEAR SAFETY SPECTACLES

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT. NOT LIKELY TO BE NEEDED

Work Hygienic Practices: GOOD PERSONAL HYGIENE PRACTICES Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASEDON ITS IGNITABILITY CHAR. THIS PRODUCT CONTAINS LEAD, WHIC

H, IF PRESENT IN WASTEAT 5.0 MG/1 OR MORE AFTER BEING EXTRACTE D, IS CONSIDERED EP TOXIC, AND THEREFOREA HAZARDOUS WASTE UNDER RCRA REGULATIONS. HAZARD WASTE NO. DOO8

Boiling Pt:B.P. Text:280-388 F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:62

Stability Indicator/Materials to Avoid:YES AVOID EX CESSIVE HEAT & SOURCES OF IGNITION. STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:NORMALLY STABLE Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY WELD/CUTTING, PRODUCES SMOKECARBON MONOXIDE/DIOXIDE. OXIDES OF LEAD CAN BE GENERATED

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME

Waste Disposal Methods: DISPOSE OF ACCOD FED, STATE & LOCAL LAWS. INCIN ONLY

EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSECONTAIN. OBSERVE PRECAUTIONS FOR FLAMM DISPOSAL. CONTAM ABSORB DISPOSE IN HAZARDOUS WASTE LANDFILL. IN ACCORD W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all li

ability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.