View NSN Online: https://aerobasegroup.com/nsn/8010-00-841-1242

Product ID: ENAMEL ALKYD S.G. GRAY 26173 ID745016 MSDS Date:03/31/1986 FSC:8010 NIIN:00-841-1242 MSDS Number: BHMWR === Responsible Party === Company Name: PRATT & LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Preparer's Name:W.A. ELLISON CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 2 MM HG @ 20C) CAS:8032-32-4 OSHA PEL:500 PPM 2950 MG/CU.M ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:BARIUM COMPOUNDS CAS:7440-39-3 OSHA PEL:.5000 MG/CU.M. ACGIH TLV:.5000 MG/CU.M.

Ingred Name:IRON OXIDE CAS:1309-37-1 OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:VOC. ORGANIC CMPD 3.7 LB/GAL LESS WATER & NPRS\* 444 G/L LESS WATER VOC. 8.6 LB/GAL SOLIDS 1032 G/L SOLIDS CALCU RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Repor

ts of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED/REPEATED EXP TO CRYSTALLINE SILICA-PNEUMOCONIOSIS, PROGRESSIVE DISABLELUNG DISEASE. MAY CAUSE PERMANENT BRAIN & NERVOUS SYS DAM. INTENTIONAL MISUSE BYDELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Explanation of Carcinogenicity:MANUFACTURER CONCLUDES THAT THERE IS NO SIGNIFICANT HAZARD FOR MAN.

Effects of Overexposure:SWALLOW: GASTROINTESTINAL IRRI, NAUSE A, VOMIT,

ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FATAL. INHAL: NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERV SYS DEPRESSION CHAR HEADACHE, DIZZ, NA USEA & CONFUSION. EYE: IRRI. SKIN: DEFATTNG AND IRRITATION OF THE SKIN. INHAL: ANESTHETIC, EVEN ASPHYXIATION

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH AIR I

MMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUIET. GET MED ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS, FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECT AREA W/SOAP & WTR. OBTAIN MED ATTN. IRRI PERSISTS.

Flash Point:80 F/26.67 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE,ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRES. POLYMER FOAM

PERFER

Fire Fighting Procedures:WEAR SCBA. WATER MAY BE INEFFECTIVE, USED TO COOL TO PREVENT PRESSURE BUILD UP AUTO-IGNITE/EXPLOSION FROM HEAT. IF WATER IS USED FOG NOZZLES ARE PREFERRED.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT,ELEC EQUIP,SPARKS, ETC. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures: ELIMINATE ALL SOURCES OF IG

NITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQUID TO COVER METAL CONTAIN FOR RECOVERY/DISPOSAL. USE NON SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS,STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORB

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINER AFTER EACH USE. DO NOT TAKE INTERNALLY.

Other Pr

ecautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. WASH HANDS & FACE THOROUGHLY BEFORE EATING OR DRINKING. EMPTY CONT MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONT SHOULD BE GROUDED/BONDED TO RECEIVING CONT. DO NOT WELD, BRAZE, ETC.

Respiratory Protection: GENERAL EXPOSURE TO ORGANIC CHEM MAY NOT REQUIRE THE USE OF RESPIR PROTECTION IFWELL VENT AREA. RESTRICTED VENT: NIOSH APPROVED CHEM CA

RTRIDGE RESPIR MAY BE REQUIRED. UNDER

SPRAYING: MECH PREFILTER. C ONFINED AREA: AIR SUPPLIED RESPIRATOR Ventilation:GEN DILUTION/LOCAL EXHAUST VENT SUFFICIENT VOL/PATTERN KEEP CONCEN HAZARD INGRED BELOW THE LOWEST EXPOSURE LIMIT

Protective Gloves:SOLVENT IMPERMEABLE GLOVE

Eye Protection: WEAR SAFETY SPECTACLES

Other Protective Equipment: AS REQUIRED TO PREVENT SKIN CONTACT

Work Hygienic Practices: WASH HANDS AND FACE THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

т

HIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASEDON ITS IGNITABILITY CHAR. THIS PRODUCT CONTAINS LEAD, WHICH, IF PRESENT IN WASTEAT 5.0 MG/1 OR MORE AFTER BEING EXTRACTE D, IS CONSIDERED EP TOXIC, AND THEREFOREA HAZARDOUS WASTE UNDER RCRA REGULATIONS. HAZARD WASTE NO. DOO8

HCC:F4 Boiling Pt:B.P. Text:148-395 F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Stability Indicator/Materials to Avoid:YES

AVOID EXCESSIVE HEAT & SOURCES OF IGNITION. STRONG ACIDS OR ALKALINE MATERIALS

Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/CARBON DIOXIDE. OXIDES OF LEAD-GENERA

Waste Disposal Methods:DISPOSE OF IN ACCOR DANCE W/FEDERAL,STATE, &

LOCAL REGULATION. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. CONTAMINATED ABSORBENT DISPOSE IN HAZARDOUS WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability fo

r its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.