

ELE CORP., THE -- PAINT REMOVER -- 8010-00-943-7127

=====
Product Identification
=====

Product ID:PAINT REMOVER

MSDS Date:09/15/1988

FSC:8010

NIIN:00-943-7127

MSDS Number: BHMZM

=== Responsible Party ===

Company Name:ELE CORP., THE

Address:7847 WEST 4TH STREET

Box:34837

City:LYONS

State:IL

ZIP:60534

Country:US

Info Phone Num:312-442-9100

Emergency Phone Num:312-442-9100

Preparer's Name:PAT E. SMI

TH

CAGE:0ET57

=== Contractor Identification ===

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

Company Name:ELE CORP., THE

Address:7847 WEST 4TH STREET

Box:34837

City:LYONS

State:IL

ZIP:60534

Country:US

Phone:312-442-9100

CAGE:0ET57

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8

050000
Fraction by Wt: 70%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 1%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 10%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LB
S
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM CHROMATE
CAS:7775-11-3
Fraction by Wt: .7%
OSHA PEL:.5 PPM
ACGIH TLV:.5 PPM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:AMMONIUM HYDROXIDE
CAS:64-11-7
Fraction by Wt: 4%
OSHA PEL:25 PPM
ACGIH TLV:25 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:INHALATION: MAY INDUCE NARCOSIS,
DIZZINESS, NAUSEA. SKIN: MAY BE
CORROSI

VE TO SKIN AND CAUSE SCARRING WHICH DISAPPEARS IN 1-2
YEARSEYES: MAY BE CORROSIVE TO EYES. CAN CAUSE HAZY VISION WHICH
WILL RETURN TONORMAL.

Effects of Overexposure:INHALATION: MAY INDUCE NARCOSIS, DIZZINESS,
NAUSEA EYES: MAY BE CORROSIVE TO EYES.
CAN CAUSE HAZY VISION WHICH RETURNS TO NORMAL SKIN: MAY BE
CORROSIVE TO SKIN AND CAUSE SCARRING WHICH DISAPPEARS IN 1-2
YEARSABSORPTION THROUGH SKIN MAY CAUSE SLIGHT PAIN AND DISCOMFORT.

=====
First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES, SEEK MEDICAL
ATTENTION. SKIN: FLUSH WITH WATER FOR 10 MINUTES.
WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH
AIR, IF UNCONSCIOUS, GIVE OXYGEN AND SEEK MEDICALATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:NA
Fire Fighting Procedures:SELF CONTAINED BREATHING APP
ARATUS REQUIRED
Unusual Fire/Explosion Hazard:CONTACT WITH FLAME MAY PRODUCE TOXIC
CHLORIDE FUMES AND/OR PHOSGENE GAS.

===== Accidental Release Measures =====

Spill Release Procedures:ALLOW TO EVAPORATE, SWEEP UP RESIDUE WITH
SAWDUST OR SWEEPING COMPOUND.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS REQUIRED IF
LIMITS ARE EXCEEDED DURING MATERIAL TRANSFER OR SPILL, OR

MATERIAL USE.

Ventilation:10 FOOT MINIMUM DURING MATERIAL TRANSFER OR SPILL
100 FOOT MINIMUM DURING MATERIAL USE

Protective Gloves:POLYETHYLENE

Eye Protection:FACE SHIELD OR GOGGLES

Other Protective Equipment:FULL WASHRACK GEAR

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:B.P. Text:115F

Vapor Pres:200 MM HG

Vapor Density:2

Spec Gravity:1.2

pH:12

Evaporation Rate & Reference:1

Solubility in Water:IN

SOL.(DISPERSABLE)

Appearance and Odor:VISCOUS, PUNGENT LIQUID

Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

STRONG ALKALIS, STRONG ACIDS, STRONG OXIDIZERS.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT FEDERAL, STATE AND LOCAL REGULATORY
AGEN- CIES FOR PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.