

DEFT, INC. -- MIL-C-83286 G/S GREEN 34102 -- 8010-01-104-6537

=====
Product Identification
=====

Product ID:MIL-C-83286 G/S GREEN 34102

MSDS Date:03/10/1987

FSC:8010

NIIN:01-104-6537

Kit Part:Y

MSDS Number: BHNCS

=== Responsible Party ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVENUE

City:IRVINE,

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:714-474-0400

CAGE:DO188

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714

Phone:800-424-9300

CAGE:DO188

=====
Composition/Information on Ingredients
=====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 25%

OSHA PEL:S,100 PPM

ACGIH TLV:S

, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 15%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:VAPORS ARE IRRITATING TO
EYES,NOSE,& THROAT.INHAL

ATION MAY CAUSE HEADACHE,DIFFICULT

BREATHING & LOSS OF CONSCIOUSNESS.CHRONIC:PROLONGED CONTACT WILL
CAUSEDRYING & CRACKING OF THE SKIN DUE TO DEF ATTING ACTION.SKIN
SENSITIZATION,ASTHMAOR OTHER ALLERGIC RESPONSES MAY DEVELOP.

Effects of Overexposure:INHALATION:IRRITATES RESPIRATORY TRACT & ACUTE
NERVOUS SYSTEM EPRESSION HEADACHEDIZZINESS,STAGGERING

GAIT,CONFUSION,UNCONSCIOUSNESS OR COMA.SKIN &
EYE:SWELLING,REDNESS,RASH.TEARING,REDNESS,STINGING SE NSATION.SKIN
ABSOR:DR

YING & DEFATTING CRACKED SKIN &

DERMATITIS.INGESTION:MOUTH,STOMACH & DIGESTIVE TRACT CHEMICAL PNEU

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY
DISORDERS.SKIN ALLERGIES,ECZEMA,DERMATITIS.

=====
===== First Aid Measures =====

First Aid:INHALATION:MOVE TO FRESH AIR.RESTORE BREATHING.SKIN:REMOVE
CONTAMINATED CLOTHINGWASH AFFECTED AREA W/SOAP & WTR.WASH CONT
CLOTHING BEFORE REUSE.EYES:FLUSH W/WTRFOR AT LEAST 15
MINS,OCCASI

ONALLY LIFTIN G EYELIDS.INGESTION:DO NOT INDUCE

VOMITING.DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS
PERSON.OBTAIN MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:23F/-5.00C

Lower Limits:1.7%

Upper Limits:11.5%

Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL,
WATER FOG

Fire Fighting Procedures:FULL FIRE FIGHTING EQUIP W/SCBA & FULL
PROTECTIVE CLOTHING SHOULD BE WORN BY FIRE FIGHT

ERS.WTR MAY BE USED

TO COOL CNTS TO PREVENT PRSR BUILD-UP,AUTO-IGN OR EXP

Unusual Fire/Explosion Hazard:KEEP CNTS TIGHTLY CLOSED.ISOLATE FROM HEAT,SPARKS,ELEC EQUIP & OPEN FLAME.CLOSEDCNTS MAY EXPLODE WHEN EXPOSED TO HEAT.APP TI HOT SUR REQUIRES SPECIAL PRECAUTION

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA.REMOVE ALL SOURCES OF IGNITION(FLAME,SPARK SOURCES,HOT SURFACES).VENTILATE AREA.CONTAIN & REMOVE WITH INER T ABSORBENT & NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106.AVOID STORING NEAR HIGH TEMPS,FIRE,OPEN FLAMES, & SPARK SOURCES.STORE IN TIGHTLY CLOSED CNTS.

Other Precautions:KEEP CNTS TIGHT & UPRIGHT TO PREVENT LEAKAGE.PREVENT PROLONGED OR REPEATED BREATHING OF VAPORS OR SPRAY MISTS.PROLONGED OVEREXPOSURE MAY CAUSE AN ALLERGIC REACTION.AVOID CONTACT W/S KIN & EYE.DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR THAT IS RECOMMENDED OR APPROVED FOR USE IN AN ORGANIC VAPOR ENVIRONMENT(AIR PURIFYING OR FRESH AIR SUPPLIED)IS NECESSARY.OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE. VENTILATION SHOULD BE PROVIDED TO KEEP EXPSURES BELOW LIMITS.

Ventilation:YES

Protective Gloves:NEOPRENE, RUBBER, POLYETHYLENE

Eye Protection:SAFETY GLASSES,CHEM GOGGLES FACE S HIELD

Other Protective Equipment:USE LONG SLEEVE & LONG LEG CLOTHING.REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM.SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 - 313F

Vapor Density:>AIR

Spec Gravity:1.2

Evaporation Rate & Reference: