

GARDINER SOLDER COMPANY DIV GARDINER METAL CO -- TIN LEAD ANTIMONY ALLOY,WW-300  
CORE;#196 -- 3439-00-239-2939

=====  
Product Identification  
=====

Product ID:TIN LEAD ANTIMONY ALLOY,WW-300 CORE;#196  
MSDS Date:08/01/1989  
FSC:3439  
NIIN:00-239-2939  
MSDS Number: BQHHS  
=== Responsible Party ===  
Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO  
Address:4820 S CAMPBELL AVE  
City:CHICAGO  
State:IL  
ZI  
P:60632-1494  
Country:US  
Info Phone Num:312-424-9300  
Emergency Phone Num:312-847-0100  
CAGE:84311  
=== Contractor Identification ===  
Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO  
Address:4820 S CAMPBELL AVE  
Box:City:CHICAGO  
State:IL  
ZIP:60632-1494  
Country:US  
Phone:312-847-0100 CHEMTREC AFTER HOURS  
CAGE:84311

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 M  
G/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)  
CAS:7440-36-0  
RTECS #:CC4025000  
OSHA PEL:0.5 MG/M3  
ACGIH TLV:0.5 MG SB/M3; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TIN  
CAS:7440-31-5  
RTECS #:XP7320000  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3; 9192

Ingred Name:ROSIN ACID  
CAS:8050-09-7

RC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:HEALTH STUDIES HAVE SHOWN THAT POTENTIAL HEALTH RISKS MAY VARY BY INDIVIDUAL.MINIMIZE EXPOSURE AS METAL FUMES.METALLIC TASTE IN MOUTH AND MAY CAUSE IRRITATION OF RESPIRATORY TRACT.MAY EFFECT CNS LIKE HEADACHE,NAUSEA,VOMITING,DIZZINESS.

Explanation of Carcinogenicity:DATA PER MSDS

Effects of Overexposure:EXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE , THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. WATERY EYES, HEADACHE, BREATHING DIFFICULTY, FREQUENT COUGHING AND/OR CHEST PAINS MAY OCCURE FROM ACUTE EXPOSURE. TOXIC GASES CAN BE FATAL.

Medical Cond Aggravated by Exposure:SOME WORKERS MAY BE AFFECTED BY A PRE-EXISTING CONDITION OR OTHER OCCUPATIONAL ILLNESS BECAUSE OF THE WIDE VARIATION IN INDIVIDUAL SUSCEPTIBILITIES.

===== First Aid Measures =====

First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES

AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING.

Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS

GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY.

THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED.

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:3164F,1740C

Melt/Freeze Pt:M.P/F.P Text:361F,183C

Vapor Pres:1 MMHG

Spec Gravity:8.55

Solubility in Water:INSOLUBLE

Appearance and Odor:SILVER GREY SOLID,ODORLESS

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condit

ion to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Products:METAL FUMES AT 361F

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate

and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.