View NSN Online: https://aerobasegroup.ae/nsn/8010-00-756-2411

PRATT & LAMBERT, INC. -- ADDUCT FOR FLAT COLOR COMP B PART 2 OF 2 -- 8010-00-756-2411

========= Product Identification ============

Product ID:ADDUCT FOR FLAT COLOR COMP B PART 2 OF 2

MSDS Date:01/16/1989

FSC:8010

NIIN:00-756-2411

Kit Part:Y

MSDS Number: BHQTZ === Responsible Party ===

Company Name: PRATT & LAMBERT, INC.

Box:2153 City:WICHITA State:KS ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:316-733-1361 Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 10%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:4

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER

CAS:107-98-2

RTECS #:UB7700000 Fraction by Wt: 65%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

Ingred Name: VOC. ORGANIC CMPD 5.7 LB/GAL LESS WATER & NPRS* 684 G/L

LESS WATER VOC. 24.4 LB/GAL SOLIDS 2928 G/L SOLIDS CALCU

RTECS #:9999999VO

========= Hazards Identification ============================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO

OSHA:NO

Health Hazards Acute and Chronic:ASPIR. OF MATL INTO LUNG MAY CAUSE CHEM. PNEUMONITIS CAN BE FATAL. HIGH CONCENTRATION MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. OVEREXPOSURE TO SOLVENTCAN CAUSE PERMANENT BRAIN & NERVOUS SYST EM DAMAGE. INTENTIONAL MISUSE CAN BEHARMFUL OR FATAL.

Effects of Overexposure: EYE: MAY CAUSE IRRITATION.

SKIN: MAY CAUSE DEFATTING &

IRRITATION OF SKIN. INHAL:

ANESTHETIC, NOSE & THROAT IRRIT., H

EADACHE, DIZZINE

SS, CONFUSION, NAUSEA, UNCONSCIOUSNESS, & ASPHYXIATION;

INGST: GASTROINTESTINAL IRRIT., NAUSEA, & VOMITING

First Aid:EYE: FLUSH W/LG AMNTS OF WTR FOR 15 MINS,LIFTING EYELIDS,GET MEDICAL ATTENTION SKIN: WASH AFFECTED AREA W/SOAP & WTR,REMOVE CONTAMINATED CLOTHES,GET MED. ATTN.INHAL: REMOVE TO FRESH AIR IMMEDIATELY,G IVE ARTIFCL RESPIRATION IF NEEDED, KEEPWARM & QUIET,GET MEDICAL ATTENTION IMMEDIATELY

INGST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY!!

Flash Point:53F/11.67C

Extinguishing Media: USE NFPA CLASS BE FIRE EXTINGUISHERS. POLYMER FOAM IS PERFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SCBA. WTR MAY BE INEFFECTIVE,MAY BE USED TO COOL EXPOSED CONTAINERS TO PRE-VENT PRESS. BUILDUP & POSS. IGN. W/EXPSD TO EXTRM HEAT.W/WTR FOG NOZZLES PREFERD Unusual Fire/Explosion Hazard:EMERG COND OVE

HEALTH HAZARD. SYMP MAY NOT BE IMMED. APPARENT. OBTAIN MEDICAL ATTENTION. WARNING!! FLAMMABLE
========= Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE & CONTAIN SPILL W/INERT MATERIAL. USE NON SPARKING TOOL ONLYPLACE ABSORBENT DIKING MATL IN COVERED METAL CONTAINER FOR DISPOSAL. PREVENT CONTAMINATION OF SEWERS STREAMS,GROUNDWATER W/SPILLED MATL OR USED ABSORB
====== ======= Handling and Storage ====================================
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LG QTYS IN COM-PLIANCE W/OSHA 29CFR1910.106. CLOSE CONTAINERS AFTER EACH USE. NEVER USE PRESSURE TO EMPTY. Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. EMPTY CONTAINERS MUST NOT BE WASHED & REUSED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER. DO NOT WELD,BRA ZE OR CUT ON EMPTY CONTA INERS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:RESTRICTED AREAS US NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING USE AMECHANICAL FILTER RESPIRATOR. CONFINED AREAS USE A NIOSH APPROVED AIR SUPPLIED RESPIRATOR. Ventilation:LOCAL EXHAUST VENTILATION OR GENERAL DILUTION Protective Gloves:SOLVENT IMPERMEABLE GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EA TING OR DRINKING Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:179-248F Vapor Density:> AIR Evaporation Rate & Dercent Volatiles by Volume:76
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION Hazardous Decomposition Produc

REXPOSURE DECOMP PROD CAUSE

ts:BURNING, INCLUDE W/HEATED BY WELD OR
CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.