

LITTON ELECTRON DEVICES -- L5644-56 TRAVELING WAVE TUBE -- 5960-01-153-8780

=====
Product Identification
=====

Product ID:L5644-56 TRAVELING WAVE TUBE

MSDS Date:12/01/1988

FSC:5960

NIIN:01-153-8780

MSDS Number: BHTKJ

=== Responsible Party ===

Company Name:LITTON ELECTRON DEVICES

Address:960 INDUSTRIAL ROAD

City:SAN CARLOS

State:CA

ZIP:94070

Info Phone Num:(415) 591-8411

Emergency Phone Num:(415) 5

91-8411

CAGE:FO469

=== Contractor Identification ===

Company Name:LITTON ELECTRON DEVICES

Address:960 INDUSTRIAL RD

City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Phone:415-591-8411

CAGE:FO469

Company Name:LITTON ELECTRON DEVICES .

Address:960 INDUSTRIAL RD

Box:City:SAN CARLOS

State:CA

ZIP:94070

Country:US

Phone:650-591-8411

CAGE:80080

=====
Composition/Information on Ingredients
=====

Ingred Name:BERYLLIUM OXIDE

CAS:1304-56-9

RTECS #:DS4025000

OSHA PEL:2 UG/CUM

ACGIH TLV:2 UG

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: DUST MAY CAUSE LUNG
DISEASE, COUGH, CHEST PAINS, SHORTNESS OF BREATH, WEIGHT LOSS,
WEAKNESS & FATIGUE. PRODUCT AS SUPPLIED IS NON-HAZARDOUS.
Explanation of Carcinogenicity:THE NATIONAL TOXICOLOGY PROGRAM HAS
LISTED BERYLLIUM OXIDE AS A POTENTIAL CANCER HAZ
ARD.
Effects of Overexposure:INHALATION: DUST MAY CAUSE LUNG DISEASE, COUGH,
CHEST PAINS, SHORTNESS OF BREATH, WEIGHT LOSS, WEAKNESS & FATIGUE.
PRODUCT AS SUPPLIED ARE NON-HAZARDOUS.
Medical Cond Aggravated by Exposure:LUNG DISEASE

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE & CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Fire Fighting Procedures:NONE
Unusual Fire/Explosion H
azard:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:IF USE OR HANDLING DIFFERS FROM NORMAL
USAGE OF SHIPPED PRODUCT. CONTACT SUPPLIER FOR ASSISTANCE IN
ESTABLISHING SAFE PROCEDURES.
Other Precautions:DON'T CRUSH, GRIND OR SAND BLAST BEO.

=====
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F

.P Text:4620F

Spec Gravity:2.86

Appearance and Odor:WHITE SOLID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:TEMPERATURES >2200F

Hazardous Decomposition Products:BERYLLIUM HYDROXIDE/OXIDE

===== Disposal Considerations =====

Waste Disposal Methods:SOLID FORMS MAY BE LAND FILLED.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.