View NSN Online: https://aerobasegroup.ae/nsn/8010-00-297-3819

CHEMRAY COATING CORP -- ENAMEL PHENOLIC OUTSIDE OLIVE DRAB 34088 -- 8010-00-297-3819

Product ID: ENAMEL PHENOLIC OUTSIDE OLIVE DRAB 34088 MSDS Date:04/02/1990 FSC:8010 NIIN:00-297-3819 MSDS Number: BHVSC === Responsible Party === Company Name: CHEMRAY COATING CORP Address:209 N MICHIGAN AVE City:KENILWORTH State:NJ ZIP:07033 Country:US Info Phone Num:201-245-1111 Е mergency Phone Num:800-424-9300 (CHEMTREC) Preparer's Name: FRED ARMSTRONG CAGE:33832 === Contractor Identification === Company Name: CHEMRAY COATING CORP Address:209 N MICHIGAN AVE Box:City:KENILWORTH State:NJ ZIP:07033 Country:US Phone:201-245-1111 CAGE:33832 Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000

Fraction by Wt: 29% OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

Ingred Name: VOC=3.09 LBS/GAL OR 371 GRAMS/LITE

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (> THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT MAY CAUSE HEADACHES A ND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS. Effects of Overexposure

:OVEREXPOSURE-NAUSEA, HEADACHE, DIZZINESS CAUSED BY OVER INHALATION. HIGH VAPOR CONCENTRATIONS (> THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT MAY CAUSE HEADACHES A ND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure:NONE GENERALLY KNOWN.

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINUTES OR UNTIL IRRITATION

SUBSIDES. IF IRRITATION PERSISTS, CALL PHYSICIAN. SKIN CONTACT; REMOVE CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WATER. INHALATIO N: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Flash Point Method:SCC Flash Point:103 F/40 C Autoignition Temp:Autoignition Temp Text:473 F Lower Limits:0.9 Upper Limits:7 Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL. Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT. COOL ENCLOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPORS OR FUMES. Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER

SPRAY TO DISPERSE THE VAPORS FROM FIRE FIGHTERS.

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDU ST) TO SPILL.

VENT AREA (OPEN WINDOWS, DOORS). LARGE SPILL: KEEP PRODUCT FROM ENTERING SEWERS/WATERCO URSES BY DIKING. ADVISE AUTHORITIES IF DOES ENTER.

Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES. KEEP IN COOL, DRY, WELL VENTILATED AREAS. AVOID DIRECT SUNLIGHT & EXTREME TEMPERATURES, HOT OR COLD.

Other Precautions: AVOID EYE, SKIN CONTACT, INHALATION OR INGESTION OF MISTS, SPRAY OR

VAPORS. AVOID BREATHING SANDING OR BLASTING DUST.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREAS.

Ventilation:LOCAL EXHAUST: FACE VELOCITY 60FPM. SPECIAL: USE ONLY W/ADEQUATE VENTILATION. MECHANICAL: USE EXPLOSION PROOF EQUIPMENT. Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:SPLASH GOGGLES OR FACE SHIELDS. Other Protective Equipment:USE CHEMICAL RESISTANT APR ON OR CLOTHING.

Supplemental Safety and Health

Boiling Pt:B.P. Text:308 F,155 C Melt/Freeze Pt:M.P/F.P Text:0 F(-17.8C) Decomp Temp:Decomp Text:600 F(316C) Vapor Pres: