View NSN Online: https://aerobasegroup.ae/nsn/8010-00-298-2288

Product ID:WHITE ALKYD ENAMEL ID X-4609 MSDS Date:07/11/1988 FSC:8010 NIIN:00-298-2288 MSDS Number: BHWSS === Responsible Party === **Company Name: UNION CARBIDE CORPORATION** Address:39 OLD RIDGEBURY ROAD City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:ROUTINE INFO CONTACT LO CAL SUPPLIER Emergency Phone Num:1-800-822-4357 CANADA 514-640-6400 CAGE:36346 === Contractor Identification === Company Name: HAMPTON ROADS SUPPLY UNION CARBIDE LINDE DIVISION Address:3450 VIRGINIA BEACH BLVD Box:12567 City:NORFOLK State:VA ZIP:23502-3123 Country:US CAGE:7D711 Company Name: UNION CARBIDE CORP LINDE DIV Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06817-0001 Country:US Phone:800-822-4357; 304-744-3487 CAGE:36346

======= Composition/Information on Ingredients

\_\_\_\_\_

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 1 MM HG @ 20 C) CAS:64475-85-0 RTECS #:PY8240000 OSHA PEL:500 PPM ACGIH TLV:100 PPM

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazar ds Acute and Chronic:ACUTE: LEAD INTOXICATION AND INHALATION CHRONIC: INGESTION Explanation of Carcinogenicity:LISTED AS SUSPECTED CARCINOGENIC POTENTIAL TO MAN. Effects of Overexposure:EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION SKIN: IRRITATION, DERMATITIS INHALATION: NASAL AND RESPIRATORY IRRITA TION, DIZZINESS, WEAKNESS, NAUSEA,HEADACHE, INGESTION: NAUSEA, VOMITING, DIARRHEA, ASPIR INTO LUNGS CAN CHEM PNEUM

\_\_\_\_\_

First Aid:EYE: FLUSH W/LARGE QTYS OF WTR, LIFTING UPPER/LOWER LIDS FOR 15 MINUTES SKIN: THOROUGHLY WASH EXPOSED SKIN W/SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR IMMEDIAT ELY IF BREATHING HAS STOPPED GIVE CPR .INNGESTION: DO NOT INDUCE VOMITING KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

Flash Point Method

:TCC Flash Point:107F/41.67C Lower Limits:1.00 Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICALS FOR SMALL FIRES, FOAM FOR LARGE FIRES Fire Fighting Procedures: CLOSED CONTAINERS MAY BUILD EXPLOSIVE PRESSURE FROM HEAT, VAPORS ARE MORE THAN AIR AND MAY TRVL AT GROUND OR MAY MOVE BY VENT AND IGNITE BY PILOT LIGHTS OR Unusual Fire/Explosion Hazard: OTHER FLAMES, SPARKS HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE OR IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL H ANDLING POINT. Spill Release Procedures: KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION SOURCES DIKE AND CONTAIN SPILL W/INERT MATERIAL SUCH ASSAND OR EARTH. TRANSFER LIQS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL, OR REMOVE WITH INERT ABSORBENT USE ONLY NON-SPARKING TOOLS. Respiratory Protection: USE SELF-CONTAINED BREATHING APPARATA **US WHERE** CONCENTRATIONS MAY BE ABOVE TLV LIMTS. BELOW TLV LIMITS, USE A NIOSH APPROVED VAPOR RESPIRATOR. Ventilation:LOCAL EXHAUST Protective Gloves: CHEMICAL GLOVES Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS Other Protective Equipment: EYE BATH AND SAFETY SHOWERS, TO PREVENT REPEATED OR PROLONG ED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:3 23-390F Vapor Density:>THAN AIR Solubility in Water: