

CON-LUX COATINGS, INC. -- ENAMEL ALKYD GLOSS WHITE 17875 -- 8010-00-664-4761
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS WHITE 17875

MSDS Date:12/29/1986

FSC:8010

NIIN:00-664-4761

MSDS Number: BHXCC

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:(206) 287-4000

Emerge

ncy Phone Num:(206) 287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

VAPOR PRESSURE 2 MM HG @ 20C

CAS:64742-47-8

Fraction by Wt: 40.39%

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDU

ST
ACGIH TLV:10 MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:IRRITATION OF EYES AND SKIN MAY OCCUR WITH
OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE
RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA AND DIZZINESS.

=====
First Aid Measures
=====

First Aid:INHALATION: REM
OVE TO FRESH AIR. RESTORE RESPIRATION IF
NECESSARY. TREAT SYMPTO-MATICALLY. EYE CONTACT: FLUSH IMMEDIATELY
WITH COPIOUS QUANTITIES OF WATER FOR 15 MIN. DERMAL CONTACT: WASH
AFFECTED AR EAS WITH SOAP AND WATER. REMOVE CONTAMI-NATED CLOTHING.
INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE.DO NOT
INDUCEVOMITING. IF SPONTANEOUS VOMITING OCCURS KEEP HEAD AT/BELOW
KNEE LEVEL.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flas
h Point:105F 40.56C
Lower Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE
EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED
CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.
WEAR
APPROPRIATE PERSONAL PROTECTION EQUIP. AND APPROVED
RESPIRATORCONTAIN SPILL WITH ABSORBENT MATERIAL & PUT INTO VAPOR
TIGHT CONTAINERS. PREVENT MATERIAL FROM CON- TACTING ANY WATER
SOURCES OR SEWERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN AREAS DESIGNED TO COMPLY WITH
ANSI/NFPA 30 FLAMMABL AN COMBUIBLE LIQUIDS CODE.
Other Precautions:GROUND CONTAINERS WHEN POURING LIQUIDS AND POWDERS TO
AVOID

STATIC CHARG BUILD UP. DO NOT HANDLE UNTIL MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. PROVIDE ADEQUATE VENTILATION/ RESPIRATORY PROTECTION TO REMOVE DECOMP.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN OPEN AREAS, USE APPROVED RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENTILATION AREAS USE APPROVED RESPIRATOR DESIGN TO REMOVE A COMBINATION OF PARTICLES AND VAPORS.

Ventilation: SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, SHOULD BE PROVIDED.

Protective Gloves: IMPERVIOUS TYPE

Eye Protection: SAFETY EYE WEAR

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM FACILITIES.

Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 148 - 323F

Vapor Density: HEAVIER

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 58.59

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXIDIZING AGENTS

Stability Condition to Avoid: EXTREME HEAT, SPARKS, OR OPEN FLAMES.

Hazardous Decomposition Products: MAY CAUSE HAZARDOUS FUMES WHEN HEATED.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE

WITH FEDERAL, STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability
of this information to their
particular situation.