

PRATT & LAMBERT, INC. -- LACQUER C/N GLOSS OLIVE DRAB 14084 ID786416 -- 8010-00-985-0751
===== Product Identification =====

Product ID:LACQUER C/N GLOSS OLIVE DRAB 14084 ID786416

MSDS Date:12/15/1988

FSC:8010

NIIN:00-985-0751

MSDS Number: BHXTM

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Pho

ne Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE

CAS:9004-70-0

RTECS #:QW0970000

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

OS

HA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:LEAD CHROMATE

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:.0500 MG/CU.M.

ACGIH TLV:.0500 MG/CU.M.

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA
(VP 40 MM HG @ 20 DEG.C)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:500 PPM

ACGIH TLV:300 PPM 1350 MG

/CU.M

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ALIPHATIC HYDROCARBON

(VP 12 MM HG @ 20 DEG.C)

CAS:64742-89-8

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC. ORGANIC CMPD 5.0

LB/GAL LESS WATER & NPRS* 600 G/L

LESS WATER VOC. 19.1 LB/GAL SOLIDS 2292 G/L SOLIDS CALCU

RTECS #:9999999VO

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING: CAN CAUSE GASTROINTESTINAL

IRR/NAUSEA/VOMIT. ASPIRATION OF MAT'L MAY CAUSE CHEM PNEUMONITIS.

INHALATION: NOSE/THROAT IRRITA. HIGH CONCENTRATION M

AY CAUSE

CENTRAL NERVOUS SYSTEM DEPRESSION CHAR BY

HEADACHES/DIZZINESS/NAUSEA/CONFUSION. EYE: MAY CAUSE EYE IRRITA.

SKIN: MAY CAUSE DEFATTING AND IRRITATION.

Explanation of Carcinogenicity:NTP/IARC-CHROMIUM/CERTAIN CHROMIUM

COMPOUNDS, POTENTIAL CAR-CINOGENS. NTP-DI(2-ETHYLHEXYL)

PHTHALATE-POTEN'L CARCINOGEN.

Effects of Overexposure:REPEATED OVEREXPOSURE TO TOLUENE MAY CAUSE

LIVER DAMAGE. OCCUPATIONAL OVEREX- POSURE TO SOLVENTS ASSOCIATED

WITH PERM BRAIN/NERVOUS SYS

TEM DAMAGE. INTENTIONAL MISUSE BY
CONCENTRATING/INHALING MAY BE HARMFUL/FATAL. INSOLUBLE
CHROMATES MAY CAUSE LUNG CANCER. LEAD-BLOOD DAMAGE &
NERVOUS/URINARY/REPRODUCTIVE SYSTEMS.
Medical Cond Aggravated by Exposure: PRE-EXISTING KIDNEY CONDITIONS MAY
BE AGGRAVATED BY EXPOSURES TO LEAD.

===== First Aid Measures =====

First Aid: SWALLOWING: DO NOT INDUCE VOMITING/GET MED ATTN. INHALATION:
REMOVE TO FRESH AIR IF BREATHING HAS STOPPED
GI VE CPR. GET MED ATTN.
EYE: FLUSH W/WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS. GET MED
ATTN. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA.
OBTAIN MED ATTN IF IRR'N PERSISTS. TREATMENT REQ FOR OVER-
EXPOSURE S/B DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL
CONDITIONS.

===== Fire Fighting Measures =====

Flash Point: 20F -6.67C
Extinguishing Media: USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF
WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard: OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY
APPARENT. OBTAIN MEDICAL ATTENTION. WARNING! FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures: ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL
WITHINERT MAT'L. TRANSFER LIQ'S/ABSORBENT DIKING MAT'L IN COVERED
METAL CONT'S FOR RECOVERY/DISPOSAL. USE ONLY NON-SPARKING TOOLS.
PREVENT CONTAM OF SEWERS/ STREAMS/GROUNDWATER W/SPILLED MAT'L/USED
ABSORBENT

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29 CFR 1910.106.
Other Precautions: DO NOT BREATHE SANDING DUST OR RE

USE EMPTY CONT. DO

NOT TAKE INTERN. CONT'ER S/BGROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE OR CUT CONT'R.NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. CLOSE AFTER EA USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTILATED AREA-RESP NOT REQ. RESTRICTED VENT-NIOSH CHEMICAL CARTRIDGE MAY BE REQ. IF SPRAYING, MECH PREFILTER MAY BE REQ. IF TLV ARE EXCEEDED, USE A PROP FITTED NIOSH/MSH

A RESP W/APPROP PROTECTI ON FACTOR. SEE OSHA 29 CFR 1910.134.

Ventilation:PROVIDE DILUTION/LOCAL EXHAUST VENTILATION TO KEEP CONCENTRAOF HAZARDOUS SUBSTANCES BELOW EXPOSURE LIMITS STATED.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. SEE OSHA STANDARD FOR LEAD.

Work Hygienic Practices:WASH WITH SOAP AND WATER HANDS/FACE THOROUGHLY BEFORE EATINGOR DRINKING.

Supplemental Safety a

nd Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:181F 302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:73

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY

WELDING/CUTTING WILL PRO- DUCE SMOKE/CARBON MONOXIDE-DIOXIDE/OXIDES OF NITROGEN/LEAD.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS AND FLAME.

=====
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY.

DISPOSEONLY IAW FED/STATE/LOCAL REGS. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DIS- POSAL OF FLAMMABLE MAT'S. CONTAMINATED ABSORBENT MAY BE DISP

OSD IN A HAZARDOUS
WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this
information to their
particular situation.