

ASHLAND CHEMICAL COMPANY -- PETROLEUM WAX RUST PREVENTATIVE -- 8030-00-598-5915

=====
Product Identification
=====

Product ID:PETROLEUM WAX RUST PREVENTATIVE

MSDS Date:02/06/1988

FSC:8030

NIIN:00-598-5915

MSDS Number: BHYJR

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL COMPANY

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Info Phone Num:614-790-3333

Emergency Phone Num:606-324-11

33

CAGE:DO048

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO., ASHLAND OIL DIV.

Address:P.O. BOX 2219

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Phone:606-324-1133

CAGE:DO048

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====
Composition/Informati

on on Ingredients =====

Ingred Name:HEAVY NAPHTHENIC DISTILLATE

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 55-70%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexposure:EYE: CAN CAUSE MODERATE IRRITATION, REDNESS,
TEARING SKIN: CAN CAUSE SLIGHT

IRRITATION INHAL: CAN

CAUSE IRRITATION OF NASAL & RESPIRATORY

PASSAGESINGST: CAN CAUSE

GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, & DIARRHEA

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LG AMNTS OF WATER, LIFTING UPPER/LOWER LIDS

OCCASIONALLY,MED. ATTN.SKIN: WASH EXPOSED AREA W/SOAP & WATER.

REMOVE CONTAMINATED CLOTHING. INHAL: REMOVE INDIVIDUAL TO

FRESH AIRING ST: IMMEDIATELY DRINK TWO GLASSES OF WTR & INDUCE

VOMITING BY EITHER GIVING IPECAC SYRUP OR BY PLACING FINGER AT

BACK OF THROAT. GET MED. ATTENTION IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point:>350F/176.7C

Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

Fire Fighting Procedures:WEAR S.C.B.A. W/FULL FACEPIECE OPERATED IN

PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING
FIRES.

Unusual Fire/Explosion Hazard:WATER/FOAM MAY CAUSE FROTHING WHICH CAN
BE VIOLENT & POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER,
ESPECIALLY

IF SPRAYED INTO CONTAINERS OF HOT BURNING LIQUID

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL FROM AREA UNTIL CLEAN UP IS

COMPLETE. SHOVEL MATL INTO CONTNRS. THOROUGHLY SWEEP AREA OF SPILL

TO CLEAN UP ANY RESIDUAL MATL. LARGESPILLS PREVENT RUNOFF TO

SEWERS,STREAMS OR OTHER BODIES OF WTR. IF THIS OCCURS NOTIFY
AUTHORITIES

===== Handling and Storage =====

Other Precaution

s:CONTAINERS OF THIS MATL MAYBE HAZARDOUS WHEN EMPTIED.
SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES(VAPOR,LIQ,&/OR
SOLID) ALL HAZARD PRECAUTIONS MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS
ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATONS
ALOS PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGITIVE PRESSURE TYPE)
UNDER SPECIFIED CON DITIONS.

Venti
lation:MECHANICAL OR LOCAL EXHAUST
Protective Gloves:NEOPRENE
Eye Protection:CHEMICAL GOGGLES/SAFETY GLASSES
Other Protective Equipment:WEAR IMPERVIOUS CLOTHING & BOOTS TO PREVENT
SKIN CONTACT
Work Hygienic Practices:LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA
Vapor Pres: