View NSN Online: https://aerobasegroup.ae/nsn/6750-01-285-1767

EASTMAN KODAK COMPANY -- 817 8998 FLEXICOLOR AR DEV/REPL,PART B -- 6750-01-285-1767

Product ID:817 8998 FLEXICOLOR AR DEV/REPL, PART B MSDS Date:08/03/1994 FSC:6750 NIIN:01-285-1767 Kit Part:Y **MSDS Number: BHZHL** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: FULLER AND D ALBERT INC Address:3170 CAMBELL Box:2706 City:FAIRFAX State:VA ZIP:22031-2302 Country:US Phone:703-591-8000 CAGE:82960

Ingred Name:WATER CAS:

7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 70 - 75% Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROXYLAMINE SULFATE CAS:10039-54-0 RTECS #:NC5425000 Fraction by Wt: 25 - 30% Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:LD50(ORAL,RAT):100-200MG/KG HYDOXYLAMINE Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, GASTROINTESTINAL TRACT. ACUTE- EYES:IRRITATION. SKIN:HARMFUL IF ABSORBED THROUGH SKIN. CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. ORAL:HARMFUL IF INGESTED. INHALATI ON:LOW HAZARD FOR RECOMMENDED HANDLING.CHRONIC- BLOOD DISORDERS. Explanation of Carcinogenicity:NONE Effects of Overexposure:EYES, SKIN AND GASTROINTESTINAL TRACT

IRRITATION, ALLERGIC SKIN REACTION

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DI

SEASE INVOLVING EYES OR SKIN MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. EYES:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. HO LD EYELIDS OPEN. INHALED:REMOVE TO FRESHAIR. ORAL:IF CONSCIOUS, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNEL. CALL A PHYSICIAN/POISON CONTROL CENTER

IMMEDIATELY.

Flash Point:NONE, NONCOMBUST

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:SOLUTION CONTAINS A STRONG REDUCING AGENT. DRIED PR

ODUCT RESIDUE CAN ACT AS A REDUCING AGENT. DRYING ON CLOTHING OR OTHER MATERIALS MAY CAUSE FIRE.

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. FOR LARGE SPILLS, ABSORB SPILL WITH VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. PREVENT RUNOFF FROM ENTERING DRAINS, SEWERS OR STREAMS. Neutralizing Agent:SODIUM BICARBONATE _____ Handling and Storage Precautions: STORE IN A COOL AREA. KEEP CONTAINERS TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE MATERIALS. Other Precautions: DO NOT GET IN EYES, ON SKIN/ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. THE ROUTINE USE OF A NONALKALINE TYPE OF HAND CLEANER AND CLEANING OF WORKING SURFACES, GLOVES WILL REDUCE POSSIBILITY OF SKIN REACTION. KEEP OUT OF REACH OF CHILDREN. **Respiratory Protec** tion:NOT NORMALLY NEEDED IN CASE OF GOOD VENTILATION. Ventilation: GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR). Protective Gloves: NEOPRENE, NITRILE, OR NATURAL RUBBER Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health KEY1:C1. THIS IS A KIT WITH THREE PARTS. THIS PART B IS TO BE USED WITH PART A & PART C FOR 1 GALLON OF WORKING SOLUTION. PART A HAS NSN: 6750-01-285-1766, CAT. NO.: 815 5194; PART C HAS NSN: 6750-01-285-1765, CAT. NO.: 818 3428. HCC:C2

Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.16 pH:3.0 Solubility in Water:COMPLETE Appea rance and Odor:COLORLESS LIQUID - ODORLESS Percent Volatiles by Volume:70-75

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, COMBUSTIBLE MATERIALS, HALOGENATED MATERIALS Stability Condition to Avoid:STABLE; HOWEVER, MATERIAL IS SHOCK SENSITIVE AND CAN DECOMPOSE ABOVE 110C (230F). AVOID HEATING ABOVE ROOM TEMPERATURE.

Hazardous Decomposition Products:NITROGEN OXIDES (NOX), SULFUR DIOXIDE

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL REGULATIONS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABE L WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The U

nited States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.