View NSN Online: https://aerobasegroup.ae/nsn/6520-00-104-7617

KERR MANUFACTURING COMPANY -- F.I.T.T. LIQUID -- 6520-00-104-7617

Product ID:F.I.T.T. LIQUID MSDS Date:03/09/1988 FSC:6520 NIIN:00-104-7617 MSDS Number: BJCPQ === Responsible Party === Company Name: KERR MANUFACTURING COMPANY Address:28200 WICK ROAD City:ROMULUS State:MI ZIP:48174 Info Phone Num: (313) 946-7800 Emergency Phone Num: (313) 946-7800 CAGE:EO529 === Cont ractor Identification === Company Name: KERR CORP Address:1717 W COLLINS AVENUE Box:City:ORANGE State:CA ZIP:92867-5422 Country:US Phone:800-537-7187 CAGE:33339 Company Name: KERR MANUFACTURING COMPANY, DIVISION OF SYBRON COR Address:28200 WICK ROAD Box:City:ROMULUS State:MI ZIP:48174 Country:US Phone: (313) 946-7800 CAGE:EO529

Ingred Name:DIBUTYL PHTHALATE (SARA III) CAS:84-74-2 RTECS #:TI0875000 Fraction by Wt: 80% Other REC Limits:5 MG/CUM OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 20% Other REC Limits:1900 MG/CUM OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN/EYES: IRRITATION. INGESTION

NAUSEA & INTOXICATION. INHALATION: IRRITATION TO MUCOUS MEMBRANE, NARCOTIC.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN/EYES: IRRITATION. INGESTION: NAUSEA & INTOXICATION. INHALATION: IRRITATION TO MUCOUS MEMBRANE, NARCOTIC.

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. CALL PHYSICIAN. SKIN: WASH W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: INDUCE VOMITING & GET MED ATTN

Flash Point:15C Lower Limits:3.3% Upper Limits:19.0% Extinguishing Media:CHEMICAL FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures:WEAR RESPIRATOR (PRESSURE-DEMAND, SELF-CONTAINED BREATHING APPARATUS, NIOSH APPROVED & FULL PROTECTIVE GEAR. USE WATER SPRAY TO COOL CONTAINERS. Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL TO SOURCE OF IGNITION & FLASH BACK.

====== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA & ELIMINATE IGNITION SOURCES. WEAR RESPIRATOR & PROTECTIVE CLOTHING. DIKE & ABSORB W/INERT MATERIAL.

Handling and Storage Precautions:STORE IN A COOL, DARK PLACE. Other Precautions:USE GOOD PERSONAL HYGIENE. USE ACCORDING TO DIRECTIONS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS & RESPIRATOR. Ventilation:NONE Protective Gloves:IMPERVIOUS, NEOPRENE Eye Protection:GOGGLES Other Protective Equipment:APRON, EYEWASH Work Hygienic Practices:USE GOOD PERSONAL HYGIENE. Supplemental Safety and Health

HCC:F3 Boiling Pt:B.P. Text:173F Vapor Pres:45 Vapor Density:1.6 Spec Gravity:0.95 Evaporation Rate & amp; Reference:(BU AC = 1): 2.8 Solubility in Water:20% Appearance and Odor:CLEAR, PALE YELLOW LIQUID, PLEASAN T ODOR.

Stability Indicator/Materials to Avoid:YES ALUMINUM Stability Condition to Avoid:SOURCES OF IGNITION Hazardous Decomposition Products:ALDEHYDES, CO, CO2

Waste Disposal Methods:DON'T ALLOW TO DRAIN TO SEWER. INCINERATE LIQUID IN PROPER EQUIPMENT. DISPOSE IN ACCORDANCE W/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compili

ng agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.