

FISKE BROTHERS REFINING CO -- LUBRIPLATE "630" DERIES -- 9150-00-989-2012

=====
Product Identification
=====

Product ID:LUBRIPLATE "630" DERIES

MSDS Date:11/01/1985

FSC:9150

NIIN:00-989-2012

MSDS Number: BJFFB

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491

Emergency Phon

e Num:419-691-2491

Preparer's Name:J. F. KUHLMAN

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-THIS PRODUCT HAS A LOW ORDER OF
ACUTE TOXICITY. CHRONIC-EYES:IRRITATION. SKIN:IRRITATION.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:EYES/SKIN:IRRITATION.
Medical Cond Aggravated by Exposure:NONE.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN:REMOVE
SOILED CLOTHES & WASH WITH SOAP AND WATER. IF INJECTED UNDER SKIN,
REGARDLESS OF APPEARANCE/SIZE, CONTACT A DOCTOR IMMEDIATELY. DELAY
MAY CAUSE LOSS OF EFFECTED BODY PART. INHALATION: REMOVE TO FRESH
AIR IF OVERCOME BY VAPOR FROM HOT PRODUCT. INGESTION:CALL PHYSICIAN
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:400F,204C
Lower Limits:1 %
Upper Limits:7 %
Extinguishing Media
:USE WATER SPRAY, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE
AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH OXIDANTS. EMPTY
CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS
THEY MAY EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS & WATER COURSES.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-KEEP CONTAINER CLOSED WHEN NOT
IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAMES OR STRONG
OXIDANTS.
Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHING
& LAUNDRER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
===== Exposure Controls/Personal Protection

=====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES & VAPORS.

Protective Gloves:NITRILE GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:USE OIL RESISTANT APRONS.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING OR DRINKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>5

50F,>288C

Vapor Pres:5

Spec Gravity:0.94-0.95

Evaporation Rate & Reference: