View NSN Online: https://aerobasegroup.ae/nsn/9150-00-531-7854

GRAPHITE PRODUCTS CORP -- LS-1774 -- 9150-00-531-7854

Product ID:LS-1774 MSDS Date:08/30/1990 FSC:9150 NIIN:00-531-7854 **MSDS Number: BJFPK** === Responsible Party === Company Name: GRAPHITE PRODUCTS CORP Address: 5756 SHARON-WARREN RD Box:207 City:BROOKFIELD State:OH ZIP:44403-9507 Country:US Info Phone Num:216-394-1617 Emergency Phone Num:216-394-1617/424-9300(CHEMT REC) Preparer's Name: MICHAEL A. BROWN CAGE:60218 === Contractor Identification === Company Name: GRAPHITE PRODUCTS CORP Address: 5756 SHARON-WARREN RD Box:207 City:BROOKFIELD State:OH ZIP:44403-9507 Country:US Phone:216-394-1617 CAGE:60218

Ingred Name:MINERAL OIL CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 35-40% Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MOLYBDE

NUM DISULFIDE CAS:1317-33-5 RTECS #:QA4697000 Fraction by Wt: >60% Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG MO/M3 ACGIH TLV:5 MG MO/M3

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE-EYE: IRRITATION. SKIN: MAY CAUSE IRRITATION.CHRONIC-DERMATITIS. **Explanation of Carcinogenic** ity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN. Effects of Overexposure: EYE: IRRITATION. SKIN: POSSIBLE IRRITATION, DERMATITIS WITH CHRONIC EXPOSURE. INHALED: UNLIKELY EXPOSURE. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. First Aid:EYE:FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN.G ET MEDICAL ATTENTION.SKIN:WASH WITH SOAP & WATER/WATERLESS CLEANER.REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.IF IRRITATION P ERSISTS SEE A DOCTOR.INGESTION:NO ILL EFFECTS

EXPECTED.

Flash Point Method:COC Flash Point:>400F,>204C Autoignition Temp:Autoignition Temp Text:>600F Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures:TREAT AS PETROLEUM FIRE.DO NOT USE A SOLID

STREAM OF WATER.USE POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.COOL CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard:CAN PRODUCE OXIDES OF SULFUR.

Spill Release Procedures:REMOVE ANY SOURCE OF IGNITION.SCOOP UP EXCESS GREASE. CLEAN AREA WITH APPROPRIATE CLEANER. Neutralizing Agent:NONE.

Handling and Storage Precautions: STORE IN A COOL, & DRY PLACE.KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES, AND SPARKS. Other Precautions:NONE NOTED

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:RESPIRATORY PROTECTION WILL NOT NORMALLY BE REQUIRED. Ventilation:NORMAL ROOM VENTILATION IS NORMALLY SUFFICIENT. Protective Gloves:NEOPRENE RUBBER AS REQUIRED. Eye Protection:SAFETY GLASSES OR CHEMICAL GOGGLES Other Protective Equipment:EYE WASH STATION Work Hygienic Practices:OB

SERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

HCC:V6 Boiling Pt:B.P. Text:>570F,>299C Vapor Pres:1 Spec Gravity:1.8 Solubility in Water:NEGLIGIBLE Appearance and Odor:GRAY-BLACK GREASE, MINERAL OIL ODOR Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS Hazardous D

ecomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, & SOX

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informat ion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.