View NSN Online: https://aerobasegroup.com/nsn/8010-00-527-3201

Product ID:TT-E-489G C-12246 ORANGE GLOSS ENAMEL MSDS Date:06/15/1987 FSC:8010 NIIN:00-527-3201 **MSDS Number: BJHTY** === Responsible Party === Company Name: EVERSEAL MANUFACTURING CO., INC. Address:475 BROAD AVENUE City:RIDGEFIELD State:NJ ZIP:07657 Country:US Info Phone N um:201-943-4986 Emergency Phone Num:201-943-4986 Preparer's Name: FRANK PRIMERANO CAGE:EO432 === Contractor Identification === Company Name: CLIFTON ADHESIVE INC Address:BURGESS PL Box:City:WAYNE State:NJ ZIP:07470 Country:US Phone:201-694-0845; 973-694-0845 CAGE:79833 Company Name: EVERSEAL MANUFACTURING CO., INC. CAGE:EO432

Ingred Name:RESIN Fraction by Wt: 34%

Ingred Name: MOLYBDATE ORANGE; LEAD CHROMATE MOLYBDATE SULFATE RED

HUMAN CARCINOGEN BY IARC) 13% AS PB & 3% AS CR. CAS:12656-85-8 RTECS #:QA4660000 Fraction by Wt: ABOVE Other REC Limits:STEL 10 MG/CUM OSHA PEL:0.5 MG/CUM ACGIH TLV:5 MG/CUM Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES MINERAL SPIRITS *92/3* CAS:64742-88-7 Fraction by Wt: 43% Other REC Limits:100 PPM OSHA PEL:120 PPM ACGIH TLV:100 PPM

Ingred Name:WEIGHT PER GALLON IN POUNDS: 9.1 RTECS #:9999999WG

============

(A1

LD50 LC50 Mixture:ORAL LD50 (LAB ANIMAL): 5 G/KG (SEE SUP) Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA, & POSSIBLE UNCONSCIOUSNESS. EYES/SKIN: IRRITATION. Explanation of Carcinogenicity:SEE INGREDIENTS. Effects of Overexposure:INHALATION: LIVER OR KIDNEY DAMAGE.

First Aid:INHALATIO N: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NEEDED. SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:TCC Flash Point:105F Lower Limits:1% Extinguishing Media:FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY NOT BE SUITABLE. Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

====== Ac

Spill Release Procedures: ENSURE ADEQUATE VENTILATION. REMOVE IGNITION SOURCES. ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE SPARK-PROOF SCOOP FOR LARGE SPILLS.

Handling and Storage Precautions: AVOID EXCESSIVE HEAT OR OPEN IGNITION SOURCES. AVOID CONTACT W/EYES & SKIN.

Other Precautions:SANDING, GRINDING, BLASTING, OR WELDING OPERATIONS SHOULD BE PERFORMED ON

LY IF ADEQUATE PRECAUTIONS ARE TAKEN.

Respiratory Protection:FUME & DUST MASK OR AIR-SUPPLIED HOOD. Ventilation:ADEQUATE TO ENSURE LEL NOT ACHIEVED. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES Other Protective Equipment:CLOTHING OR BARRIER CREAM Supplemental Safety and Health LD50 INFORMATION IS FOR MINERAL SPIRITS.

HCC:F4 Boiling Pt:B.P. Text:323-3 90F Vapor Density:>1 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:61%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:EXCESSIVE HEAT OR OPEN IGNITION SOURCES Hazardous Decomposition Products:CO, CO2

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL R

EGULATIONS. COMBUSTIBLE LIQUID.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informa tion to their particular situation.