

SHELL OIL CO PRODUCT SAFETY AND COMPLIANCE -- EPON CURING AGENT R U --
8010-01-060-7176

===== Product Identification =====

Product ID:EPON CURING AGENT R U

MSDS Date:10/28/1986

FSC:8010

NIIN:01-060-7176

Kit Part:Y

MSDS Number: BJJGZ

=== Responsible Party ===

Company Name:SHELL OIL CO PRODUCT SAFETY AND COMPLIANCE

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:713-241-4819

Emerg

ency Phone Num:713-473-9461 OR 800-424-9300

CAGE:3H919

=== Contractor Identification ===

Company Name:AEROFAB CO INC.

Address:2335 GOODRICH ST

Box:City:FERNDALE

State:MI

ZIP:48220-1440

Country:US

Phone:313-542-0051

CAGE:01685

Company Name:SHELL OIL COMPANY CORPORATE ENVIRONMENTAL AFFAIRS

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:713-241-4819/713-473-9461

CAGE:3H919

Company Name:T. J. MACHINE & TOOL CORP.

Address:700 W MAIN STREET

Box:City:AZLE

State:TX

ZIP:76020

Country:US

Phone:

817-444-5548
CAGE:4K455

=====
Composition/Information on Ingredients
=====

Ingred Name:EPON CURING AGENT U
Fraction by Wt: 100%

Ingred Name:EPOXY RESIN/AMINE ADDUCT
CAS:68610-56-0
Fraction by Wt: 73%

Ingred Name:DIETHYLENE TRIAMINE
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 25%
OSHA PEL:1 PPM
ACGIH TLV:S, 1 PPM; 9192

Ingred Name:PHENOL, LD50: (ORAL) 530 MG/KG (RAT).
CAS:108-95-2
RTECS #:SJ3325000
Fraction by Wt: 2%
OSHA PEL:5 PPM/SKIN
ACGIH TLV:10 PPM/SKIN
EPA Rpt Qty:
1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

LD50 LC50 Mixture:SEE SUPP DATA
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:SEV IRRIT TO THE EYES;SKIN:MOD
TOXIC & MAY BE HARMFUL IF ABSORBED THRU THE SKIN,SEV IRRIT TO THE
SKIN, SKIN SENSITIZER,INHAL:IRRIT TO NOSE,THROAT&RESP TRACT.
VAPORS&MISTS ARE PRESUMED TO CAUSE LUN G SENSITIZAT
ION.INGEST:MOD
TOXIC AND MAY BE HARMFUL IF SWALLOWED.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:IRRITATION AS NOTED ABOVE. SKIN SENSITIZATION
(ALLERGY) MAY BE EVIDENCED BY RASHES. ESPECIALLY HIVES. LUNG
SENSITIZATION (E.G., ALLERGY, ASTHMA) MAY BE EVIDENCED BY WHEEZING
WITH SORTNESS OF BREATH AN D COUGH.
Medical Cond Aggravated by Exposure:PREEXISTING EYE,SKIN&RESP DISORDERS
MAY BE AGGRAVATED BY EXPOS TO THIS PROD. PREEXISTING SKIN/LUNG
ALLERGIE

S MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOS TO THIS PROD.

=====
===== First Aid Measures =====

First Aid:EYE:IMMED FULSH EYE W/PLENTY OF H*2O ATLEAST 15 MIN WHILE HOLDING EYELIDS OPEN.GET MD ATTN;SKIN:IMMED REMOVE CONTAM CLTH OR SHOES,WIPE EXCESS FROM SKIN&FLUSH W/PLENTY OF H*2O AT LEAST 15 MIN.DO NOT RE USE CLTH UNTIL THOROUGHLY CLEANED.GET MD.INHAL:REMOVE VICTIM TO FRESH AIR&PROVIDE O*2 IF BRTH IS DFCLT.GET MD.INGEST:DO NOT INDUCE VOMIT.DO NOT GIVE LIQ TO A VERY DROWSY,CONVL OR UNCON PERSON.SEE MD.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>200F,>93C
Extinguishing Media:USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.
Fire Fighting Procedures:EVACUATE HAZ AREA OF UNPROTECTED PERS.MATL WILL NOT BURN UNLESS PREHEATED.USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:DETA AND PHE
NOL VAPORS MAY BE RELEASED.
NITROGEN OXIDES AND NITROGEN CONTAINING ORGANIC COMPOUNDS MAY BE RELEASED UPON COMBUSTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MAY BURN ALTHOUGH NOT READILY IGNIT. USE CAUTIOUS JUDGEMENT WHEN CLEANING UP LGE SPILL. WEAR NIOSH/MSHA APPROVED RESP & PROT CLTH AS APPROP. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE & CONTAIN.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:SENSITIZER, SEV IRRIT. MINIMIZE ALL CONT W/MATL.
Other Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMP, EMPTY CNTNRS CAN HAVE HAZARDOUS PRODUCT RESIDUES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID BRTH VAPOR OR MISTS. IF EXPOS MAY OR DOES EXCEED, TLV, PEL. USE A NIOSH/MSHA APPROVED

FULL-FACE PIECE RESP TO
PVNT OVEREXPOS.

Ventilation:AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

Protective Gloves:WEAR CHEMICAL-RESISTANT GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE.

Work Hygienic Practices:WASH W/SOAP & WATER BEFORE EATING. DRINKING,
SMOKING OR USING TOILET FACILITIES. LAUNDER CONTAM CLTH BEFORE
REUSE.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====
=====

Vapor Pres:1

Spec Gravity:1.1

Solubility in Water:MISCIBLE

Appearance and Odor:LIGHT YELLOW LIQUID, AMMONICAL ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

SEE ABOVE

Stability Condition to Avoid:CAN REACT WITH STRONG OXIDIZING AGENTS AND
STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:NITROGEN OXIDES, CARBON MONOXIDE AND
UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

=====
===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN
COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its u

se. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.