

SHERWIN INC -- ER83A EMULSIFIER (HYDROPHILIC) -- 6850-01-266-4552

=====  
Product Identification  
=====

Product ID:ER83A EMULSIFIER (HYDROPHILIC)

MSDS Date:01/01/1986

FSC:6850

NIIN:01-266-4552

Kit Part:Y

MSDS Number: BJKVB

=== Responsible Party ===

Company Name:SHERWIN INC

Address:5530 BORWICK AVE

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Info Phone Num:213-861-6324

Emergency Phone Num:213-

861-6324

CAGE:21405

=== Contractor Identification ===

Company Name:SHERWIN INC.

Address:5530 BORWICK AVE.

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Phone:562-861-6324/FAX 923-8370

CAGE:21405

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SURFACTANT (NON-IONIC)

Fraction by Wt: 30-60%

Other REC Limits:NONE SPECIFIED

Ingred Name:GLYCOLS (TYPE NOT SPECIFIED)

Fraction by Wt: 30-60%

Other REC Limits:NONE SPECIFIED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:Z

C0110000

Fraction by Wt: 0.5-4%

Other REC Limits:NONE SPECIFIED

Ingred Name:DYESTUFF

Fraction by Wt: 200F,>93C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA AWAY FROM HEAT OR FLAMES. KEEP CONTAINERS CLOSED WHEN NOT IN USE. COMBUSTIBLE LIQUID; EMPTY CONTAINERS CAN BE HAZARDOUS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO MINIMIZE EXPOSURE. LOCAL EXHAUST RECOMMENDED.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:

USE CHEMICAL SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:DO NOT REUSE CONTAMINATED CLOTHING UNTIL LAUNDERED. WASH THOROUGHLY AFTER USE.

Supplemental Safety and Health

CAUTION: COMBUSTIBLE LIQUID AS SUPPLIED. USE WITH ADEQUATE VENTILATION AND AWAY FROM SPARKS, FIRE OR OPEN FLAME. HIGHLY DETERGENT. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. DANGER - CAUSES EYE BURNS. FIRST AID: FLUSH EYES WITH PLENTY OF WATER FOR AT L

EAST 15

MINUTES. CALL A PHYSICIAN.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:390F,199C

Evaporation Rate & Reference:0.1 (N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:PINK LIQUID, DETERGENT ODOR

Percent Volatiles by Volume: