

PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIVISION -- ENAMEL ALKYD GLOSS BROWN
10076 ID 742010 -- 8010-00-298-2304

=====
Product Identification
=====

Product ID:ENAMEL ALKYD GLOSS BROWN 10076 ID 742010

MSDS Date:08/23/1990

FSC:8010

NIIN:00-298-2304

MSDS Number: BJLGL

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIVISION

Address:16116 E. 13TH ST.

Box:2153

City:W

ICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

=====

Ingred Name:MINERAL SPIRITS (VP 2 MMHG @ 20C)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

Other REC Limits:LFL 1.0 UFL 7.0

OSHA PEL:100 PPM/525 MG/CU.M.

ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:LEAD CHROMATE (SARA 313) (OSHA-CEIL .1000 MG/CU.M.)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 102 F/>39 C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:USE WATER

TO COOL EXPOSED CONTAINERS TO

PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM EXTREME HEAT.

IF WATER USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE
HEALTH HAZARD. SYMPTOMS MAY BE DELAYED, OBTAIN MED. KEEP CONTAINERS
TIGHTLY CLOSED. CONTAINER MAY EXPLODE FROM EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE IGNITE SOURCES.

DIKE &

CONTAIN WITH INERT MATERIAL(SAND) TRANSFER LIQUID TO COVERED METAL

CONTAIN FOR RECOVERY/DISPOSAL. REMOVE WITH INERT ABSORBENT. USE ONLY

NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, GROUNDWATERS

WITH MATERIAL/ABSORBENT

Neutralizing Agent:N/A.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 95F. STORE LARGE AMOUNT
IN COMPLIANCE WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE
CONTAINER AFTER EACH USE. DO NOT BREATHE DUST.

Other

Precautions:EMPTY CONTAINERS MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPT Y. DRUM IS NOT A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTED AREA MAY NOT REQUIRE USE OF RSPRTR. RESTRICTED VENT:CHEM CARTRIDGE RSPRTR MAYBE REQUIRED. SPRAY:USE MECH PREFILTER. CONFINED AR
EA:USE AIR SUPPLIED RSPRTR. IF TLV EXCEED USE PROPERLY FITTED RSPRTR W/PROTECTION FACTOR
Ventilation:GEN DILUTE/LOCAL EXHAUST IN VOL/PATTERN TO KEEP CONCENTRATE OF HAZARD INGRED BELOW LOWEST LIMITS. REMOVE DECOMP PRODUCTS
Protective Gloves:SOLVENT IMPERMEABLE GLOVES.
Eye Protection:WEAR SAFETY SPECTACLES
Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. SEE OSHA STANDARD FOR LEAD.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

PRODUCT CONTAINS CHROMIUM. WASTE RESIDUE OF THIS PRODUCT MAY QUALIFY AS HAZARDOUS WASTE(40 CFR PART 261.74- CHARACTERISTIC OF EP TOXICITY). IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDOUS WAST E BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT 140F OR LESS. PROPER RCRA CLASS WOULD BE D001.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:302 TO 390F
Vapor Density:> THAN AIR
Spec Grav
ity:1.0
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELD/CUTTING, WILL PRODUCT SMOKE/CO/CO2/OXIDES OF CHROMIUM & LEAD MAY BE GENERATED. *
Conditions to Avoid P

polymerization:KEEP AWAY FROM HEAT, SPARKS, FLAME.

*WELD/TORCH CUT COATED MATERIAL MAY PRODUCE METAL OXIDES CAUSING "METAL FUME FEVER"

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. CONTAMINATED ADSORBENT MAY BE DISPOSED IN HAZARDOUS WASTE LANDFILL

LL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.