

INTERNATIONAL COATINGS CO -- ICC MAT COATINGS -- 8010-01-066-5635

===== Product Identification =====

Product ID:ICC MAT COATINGS

MSDS Date:01/01/1987

FSC:8010

NIIN:01-066-5635

MSDS Number: BJMHR

=== Responsible Party ===

Company Name:INTERNATIONAL COATINGS CO

Address:13929 F 166TH ST

City:CERRITOS

State:CA

ZIP:90701

Country:US

Info Phone Num:213-926-0747

Emergency Phone Num:213-926-0747

CAGE:INCMM

=== Contractor Identification ===

Company Name:EXPANDED RUBBER AND PLASTIC CORP

Address:14000 S WESTERN AVE

Box:City:GARDENA

State:CA

ZIP:90249-3008

Country:US

Phone:310-321-4260

CAGE:25598

Company Name:INTERNATIONAL COMMUNICATION

Address:ROUTE 119 SOUTH

Box:386

City:CONNELLSVILLE

State:PA

ZIP:15425

Country:US

Phone:412-628-1014;800-424-9300(CHEMTREC)

CAGE:INCMM

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 50%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 6%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
R
eports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:VAPOR IRRITATES EYES, NOSE & THROAT.
LIQUID WILL DAMAGE EYE TISSUES. LIQUID IS IRRITATING TO SKIN
CAUSING DERMATITIS.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. SEE MD. SKIN:WASH THOROUGH
HLY WITH
SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES. CALL MD.
INGEST:GET MD IMMED .

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:21.0F,-6.1C
Lower Limits:1.8
Upper Limits:10.0
Extinguishing Media:DRY CHEMICAL, CO*2 OR MECHANICAL FOAM
Fire Fighting Procedures:USE WATER SPRAY TO COOL SURROUNDING MATERIALS
AND SURFACES. NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE
EQUIPMENT REQUIRED FOR FIRE FIGHTING PERSONNEL.
Unus

ual Fire/Explosion Hazard:OVERHEATED CONTAINER MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ANY SOURCES OF FIRE, SPARKS, OR
OTHER IGNITION. CONTAIN SPILLED MATERIAL WITH ABSORBENT MATERIAL OR
SAND. TRANSFER TO CLOSED CONTAINERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING MIST AND VAPOR. STOR
E
IN A COOL DRY AREA PREFERABLY BELOW 90F. KEEP CONTAINERS TIGHTLY
SEALED.

Other Precautions:WARNING THESE PRODUCTS ARE FLAMMABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF NEEDED, A NIOSH/MSHA APPROVED RESPIRATOR FOR
ORGANIC VAPOR AND MIST SHOULD BE WORN.

Ventilation:LOCAL EXHAUST, MECHANICAL (GENERAL) VENTILATION
RECOMMENDED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equ

ipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND BEFORE
EATING, SMOKING OR USING SANITARY FACILITIES .

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:174F,79C

Vapor Pres:70

Vapor Density:2.4

Spec Gravity:0.84

Evaporation Rate & Reference:5 (N-BUTYL ACETATE = 1)

Solubility in Water: 20%

Appearance and Odor:SHARP PUNGENT ODOR VARIED C

OLORS

Percent Volatiles by Volume:80-90%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXPOSURE TO HIGH HEAT, OPEN FLAMES, SPARKS

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,
HYDROGEN CHLORIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF I/A/W FEDERAL, STATE
AND LOCAL REGULATI
ONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular s
ituation.