

AKRON PAINT AND VARNISH INC -- TYPE II WALKWAY NON-SLIP BLACK, G-9126 --  
8010-00-641-0427

===== Product Identification =====

Product ID:TYPE II WALKWAY NON-SLIP BLACK, G-9126

MSDS Date:07/26/1990

FSC:8010

NIIN:00-641-0427

MSDS Number: BJMZJ

=== Responsible Party ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PKY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Info Phone Num:330

-773-8911

Emergency Phone Num:330-773-8911

CAGE:70228

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETR.DISTILLATES (VP 15 MM HG) (THAN AIR MAY TRAVEL BY GROUND,ETC.

TO IGNITE SOURCE DISTANT FROM HANDLING POINT.CONTAIN(EMPTY)MAY EXPLODE.OVEREXP TO DECOMP, POSSBL DELAYED HEALTH HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:SM:ABSORB LIQ W/RAGS,ABSORB,VERMICUL,OTHER & TRANSFER TO HOOD. LG:ELIM IGNITE SOURCES.DIKE AREA.VENT AREA,PUMP LIQ INTO SALVAGE TANK,REMAIN LIQ TAKE UP W/SAND,FLOOR ABSORB,OTHER ABSORB & SHOVEL INTO C ONTAINER. PREVENT RUN-OFF TO SEWERS & BODIES OF\*

Neutralizing Agent:N/K. \*WATER. NOTIFY PROPER AUTHORITIES AS REQUIRED BY LOCAL,STATE & FED REGS.

=====

===== **Handling and Storage**=====

Handling and Storage Precautions:DO NOT DROP CONTAIN.AVOID HEAT,SPARK,OPEN FLAME. STORE LG AMNT ONLY IN BLDG DESIGNED TO COMPLY W/OSHA1910.106.NEVER USE PRESS TO EMPTY.AVOID INHALING. Other Precautions:HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR "IGNITION" TEMPERAT URES.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:IF OUTDOORS OR OPEN AREAS WITH UNRESTRICTED VENTILATION, APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATES & VAPORS. IN CONFINED AREAS, APPROVED AIR LINE TYPE RESPI RATORS OR HOODS. Ventilation:PROVIDE SUFF VENT IN VOL/PATTERN TO KEEP AIR CONTAM CONCENTRATE BELOW CURRENT APPLICABLE LIMITS. REMOVE DECOMP PRODUCTS. Protective Gloves:RESISTANT GL OVES SUCH AS NITRILE RUBBER Eye Protection:CHEM SPLASH GOGGLES OR OTHERS PERMITTED Other Protective Equipment:NORMAL PROTECTIVE CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE. Work Hygienic Practices:OBSERVE ALL PRECAUTIONS. WASH CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health CAUTION: THIS PRODUCT CONTAINS PIGMENTS WHICH MAY BECOME A DUST NUISANCE WHEN REMOVED BY SANDING, ABRADING OR SANDBLASTING. DUST MASKS SHOULD BE WORN DURING THESE OPERATIONS TO AVOID TH IS HAZARD.

===== **Physical/Chemical Properties**=====

HCC:F2  
Boiling Pt:B.P. Text:240 TO 285F  
Vapor Density:> THAN AIR  
Spec Gravity:1.33  
Evaporation Rate & Reference:6.85 X N-BUTYL ACETATE  
Appearance and Odor:BLACK LIQUID  
Percent Volatiles by Volume:51.7

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZERS (E.G. NITRIC ACID)  
Stability Condition to Avoid:KEEP AWAY FROM H

EAT AND OPEN FLAME.

Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE AND DIOXIDE,  
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
e  
xpressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.