

EXIDE CORP -- LEAD ACID BATTERY -- 6140-01-203-8983

===== Product Identification =====

Product ID:LEAD ACID BATTERY

MSDS Date:01/01/1987

FSC:6140

NIIN:01-203-8983

MSDS Number: BJQJS

=== Responsible Party ===

Company Name:EXIDE CORP

Address:9176 RED BRANCH RD

City:COLUMBIA

State:MD

ZIP:21045-2059

Country:US

Info Phone Num:301-596-2680

Emergency Phone Num:301-596-2680

CAGE:90660

=== Contractor Ident

ification ===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:ENERSYS INC

Address:8306PATUXENT RANGE RS SUITE 103

Box:City:JESSUP

State:MD

ZIP:20794-8609

Country:US

Phone:301-381-8500 OR 215-378-0757

CAGE:90660

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: >60%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 10-30%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2140 MG/KG (H2SO4)
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of
Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION OF VAPORS CAUSES SEVERE
IRRITATION OR BURNS OF THE RESPIRATORY SYSTEM, PULMONARY EDEMA, OR
LUNG INFLAMMATION. EYE CONTACT CAUSES SEVERE DAMAGE AND POSSIBLE
BLINDNESS. SKIN CONTACT CAUSES BU RNS AND POSSIBLE DEEP ULCERATION.
INGESTION CAUSES SEVERE BURNS TO MOUTH, THROAT, AND STOMACH. LEAD
POISONING POSSIBLE.
Explanation of Carcinogenicity:THIS CHEMICAL IS NOT LISTED BY IARC,
NTP, OR OSHA
AS A CARCINOGEN.
Effects of Overexposure:SEVERE IRRITATION OR BURNS TO EYES, NOSE AND
THROAT. PULMONARY EDEMA, BRONICAL EMPHYSEMA, CONJUNCTIVITIS,
STOMATITIS, DENTAL EROSION, NAUSEA AND VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MI

NUTES HOLDING EYELIDS OPEN. GET PROMPT MEDICAL ATTENTION.

SKIN :REMOVE CONTAMINATED CLOTHING. WASH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING.

GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Lower Limits:4 (H2)

Upper Limits:74.2 (H2)

Extinguishing Media:USE HALOGEN TYPE OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A

FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA PROMPTLY.

Unusual Fire/Explosion Hazard:OVERCHARGING WILL GENERATE HYDROGEN GAS AND SULFURIC ACID MIST.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. WEAR FULL PROTECTIVE EQUIPMENT. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DIKE TO RETAIN RUNOFF. NEUTRALIZE SMALL AMOUNTS WITH SODA ASH OR LIME. MAKE SLURRY AND SHOV

E L INTO DISPOSAL DRUM.

Neutralizing Agent:SODIUM BICARBONATE OR A SODA ASH/SLAKED LIME MIXTURE (50-50)

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM FLAMES DURING AND IMMEDIATELY AFTER CHARGE. DO NOT SHORT BATTERY WITH TOOLS, ETC. AVOID PROLONGED OVERCHARGING IN CONFINED AREAS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION

CONDITIONS EXIST. IF AIRBORNE CONCENTRATION EXCEEDS TLV, A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED.

Ventilation:USE SUFFICIENT MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV REQUIREMENTS.

Protective Gloves:RUBBER GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES AND FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE IMPERVIOUS WORK CLOTHING, BOOTS AND APRON AS REQUIRED.

Work Hyg

ienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:C1
Spec Gravity:1.28 (H2SO4)
pH:1
Solubility in Water:COMPLETE (H2SO4)
Appearance and Odor:ODORLESS, CLEAR OILY LIQUID ELECTROLYTE IN 12 VOLT
SEALED 7X9X
7 INCH BATTERY

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:PROLONGED OVERCHARGING IN CONFINED SPACES.
Hazardous Decomposition Products:OXIDES OF SULFUR AND HYDROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL
APPLICABLE FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS

.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situ
ation.