

PURITAN-BENNETT -- GASEOUS OXYGEN,OXYGEN GAS,GOX -- 6505-00-132-5225

=====  
Product Identification  
=====

Product ID:GASEOUS OXYGEN,OXYGEN GAS,GOX

MSDS Date:01/01/1987

FSC:6505

NIIN:00-132-5225

MSDS Number: BJQLV

=== Responsible Party ===

Company Name:PURITAN-BENNETT

Address:10800 PFLUMM ROAD

City:LENEXA

State:KS

ZIP:66215

Country:US

CAGE:45148

=== Contractor Identification ===

Company Name:PURITAN-

BENNETT

Address:10800 PFLUMM ROAD

Box:City:LENEXA

State:KS

ZIP:66215-2182

Country:US

CAGE:45148

=====  
Composition/Information on Ingredients  
=====

Ingred Name:OXYGEN

CAS:7782-44-7

RTECS #:RS2060000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HEALTH HAZARDS-ACUT



ES, SALT AND CORROSIVE

CHEMICALS. USE PRESSURE REGULATOR WHEN CONNECTING TO LOW PRESSURE PIPING. USE CHECK VALVE TO PREVENT BACKFLOW. DO NOT REFILL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE.

Ventilation:LOCAL EXHAUST. PREVENT OXYGEN CONCENTRATION OVER 25%.

Protective Gloves:LEATHER WORK GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:SAFETY TOE SHOES.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supple

mental Safety and Health

AVOID THE USE OF OIL IN CYLINDER.

===== Physical/Chemical Properties =====

HCC:G4

Boiling Pt:B.P. Text:-297F,-183C

Melt/Freeze Pt:M.P/F.P Text:-362F,-219C

Vapor Pres:ABOVE CRIT

Vapor Density:1.10

Spec Gravity:1.11

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS GAS, ODORLESS GAS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALL FLAMMABLE MATERIALS.

Stability Condi

on to Avoid:CONTACT WITH ALL FLAMMABLE MATERIALS.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF RESIDUAL OXYGEN IN COMPRESSED GAS CYLINDERS. RETURN TO MANUFACTURER WITH THE CYLINDER VALVE TIGHTLY CLOSED, POSITIVE PRESSURE IN THE CYLINDER, AND VALVE CAP IN PLACE.

Disclaimer (provided with this information by the compiling agencies):

This infor

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.