

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 9903 PRIMER -- 5970-01-084-4932

===== Product Identification =====

Product ID:CS 9903 PRIMER

MSDS Date:05/02/1989

FSC:5970

NIIN:01-084-4932

Kit Part:Y

MSDS Number: BJRHC

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Info Phone Num:818-982-1650

Emergency

Phone Num:800-424-9300 CHEMTREC

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

In

gred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty  
:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 5000 MG/KG (TOLUENE)  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:IRRITATION. SKIN:MILDLY  
IRRITATING. PROLONGED CONTACT MAY CAUSE DERMATITIS AND TISSUE  
DEFATTING. INHALATION:RESPIRATORY SYSTEM IRRITATION AND LIGHT  
HEADEDNESS. MAY CAUSE NAUSEA, HEA  
DACHE, DROWSINE SS, VOMITING.  
INGESTION:SOLVENT ASPIRATION INTO LUNGS AS A RESULT OF VOMITING MAY  
CAUSE LUNG AND DIGESTIVE SYSTEM DAMAGE  
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS  
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.  
Effects of Overexposure:VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.  
OVEREXPOSURE MAY RESULT IN FATIGUE, WEAKNESS, CONFUSION EUPHORIA,  
DIZZINESS, HEADACHE, DILATED PUPILS, LACRIMATION, NERVOUSNESS,  
MUSCLE FATIGUE, INSOMNI

A, PARESTHESIA, DERMATITIS, AND  
PHOTOPHOBIA. CAN CAUSE TEARING, REDNESS OF EYES AND BLURRED VISION.  
IRRITATION OF SKIN.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS  
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN,  
RESPIRATORY TRACT OR NERVOUS SYSTEM MAY BE AT INCREASED RISK FROM  
EXPOSURE. DRYING/CRACKING OF SKIN.

===== First Aid Measures =====

First Aid: EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING

EYELID. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP &  
WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ADVICE.  
INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION  
IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE  
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET MEDICAL  
ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 10F, -12C

Lower Limit

ts: 1.3

Upper Limits: 12.0

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. VAPORS ARE HEAVIER  
THAN AIR AND MAY TRAVEL TO DISTANT IGNITION SOURCES.

=====

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND  
REMOVE WITH INERT ABSORBENT. USE NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions: CONTENTS ARE FLAMMABLE. KEEP AWAY FROM  
HEAT, SPARKS, AND OPEN FLAME. DURING USE AND UNTIL ALL VAPORS ARE  
GONE: KEEP AREA VENTILATED-DO NOT SMOKE.

Other Precautions: AVOID BREATHING OF VAPORS.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED RESPIRATOR IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL/TLV. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:NEOPRENE OR NATURAL RUBBER GLOVES

Eye Protection:PAINT GOGGLES/SAFETY GLASSES AS REQUIRED

Other Protective Equipment:INDUSTRIAL-TYPE WORK CLOTHING, HAT AND APRON AS REQUIRED.

Work Hygienic Practices:USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY MIST. AVOID CONTACT WITH SKIN & EYES. WASH HANDS AFTER USE.

Supplemental Safety and Health

KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. STORE BELOW 80F IN

DRY AREA.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:133F,56C

Vapor Pres:180

Vapor Density:2.6 AIR=1

Spec Gravity:0.80

Evaporation Rate & Reference:7 (N-BUTYL ACETATE=1)

Solubility in Water:MISCIBLE

Appearance and Odor:CLEAR LIQUID; KETONE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, PYRIDINES, CAUSTICS, INORGANIC ACIDS, ISOCYANATES.

Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURES

Hazardous Decomposition Products:BY FIRE: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MATERIAL WILL LIKELY BE A LAND-BANNED HAZARDOUS WASTE WHICH MUST BE DISPOSED OF ACCORDINGLY. DO NOT INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATION S.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.