

MOBIL OIL CORP -- MOBIL GREASE 28 -- 9150-01-291-9223

=====
Product Identification
=====

Product ID:MOBIL GREASE 28

MSDS Date:12/08/1989

FSC:9150

NIIN:01-291-9223

MSDS Number: BJSJT

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:530 EAST SWEDES FORD ROAD

Box:839

City:VALLEY FORGE

State:PA

ZIP:19482

Country:US

Info Phone Num:703-849-3265

Preparer's Name:ENVIRONMENTL AFFAIRS DEPT

CAGE:

1E969

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Address:530 EAST SWEDES FORD ROAD

Box:1031

City:VALLEY FORGE

State:PA

ZIP:19482

Country:US

Phone:703-849-3265

CAGE:1E969

Company Name:SPD TECHNOLOGIES

CAGE:30086

=====
Composition/Information on Ingredients
=====

Ingred Name:SYNTHETIC OILS

Fraction by Wt: >70%

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ADDITIVES AND/OR OTHER INGREDIENTS

Fraction by Wt: 5 G/KG(RAT); DERM>2 G/KG(RBT)

R

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NOT EXPECTED TO BE A PROBLEM.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MIN. SKIN: WASH W/SOAP & WATER. HIGH PRESS
ACCIDENTAL INJECT THRU SKIN REQ IMMED ATTN BY MD
FOR POSS INCISION, IRRIGATION AND/OR DEBRIDEMENT. INGEST: IF >1/2 LITER (PINT) INGEST, IMMED GIVE 1-2 GLASSES OF WATER & CALL MD, HOSP EMERG RM OR POIS CTL CTR. DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. INHAL: NOT EXPECTED TO BE A (SEE SUPP DATA)

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:450F,232C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE. (SEE SUPP DATA)
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SHOVEL UP & DISPOSE OF AT APPROPRIATE WASTE DISPOSAL FACILITY. USCG REGULATIONS REQUIRE IMMEDIATE REPORTING OF SPI
LLS THAT COULD REACH ANY WATERWAY INCLUDING INTERMITTENT DRY CREEKS. (800-424-8802)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENT

ILATION.

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE
AND WITH ADEQUATE VENTILATION.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

FIRE FIGHT PROC: IN ENCLOSED AREAS USE NIOSH/MSHA APPROVED SCBA AND
FULL PROTECTIVE EQUIPMENT. PREVENT RUNOFF FROM FIRE CONTROL OR
DILUTION FROM ENTERING ST

REAMS OR DRINKING WATER SUPPLY. FIRST AID

PR OC: PROBLEM. IF NECESSARY, REMOVE TO FRESH AIR & SUPPORT
BREATHING (GIVE O*2/ARTIFICIAL RESPIRATION) .

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres: