

U.S. OIL CO., INC. -- 012210 GASOLINE PREMIUM UNLEADED -- 9130-00-148-7104

=====  
Product Identification  
=====

Product ID:012210 GASOLINE PREMIUM UNLEADED

MSDS Date:11/01/1985

FSC:9130

NIIN:00-148-7104

MSDS Number: BJVYZ

=== Responsible Party ===

Company Name:U.S. OIL CO., INC.

Address:425 S. WASHINGTON ST.

Box:25

City:COMBINED LOCKS

State:WI

ZIP:54113

Info Phone Num:(414) 739-6100

Emergency Phone

Num:(414) 739-6100

CAGE:9V710

=== Contractor Identification ===

Company Name:U S OIL CO INC

Address:558 CARTER CT

Box:City:KIMBERLY

State:WI

ZIP:54136

Country:US

Phone:920-735-8287

CAGE:9V710

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM DISTILLATE

CAS:68477-31-7

Fraction by Wt: >95%

ACGIH TLV:100 PPM

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 1-5%

Other REC Limits:16 MG/CUM

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TL

V:10 PPM; A2; 9192  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:SKIN: IRRITATION, DEFATTING, &  
DERMATITIS. EYE: IRRITATION, REDNESS, TEARING, & BLURRED VISION.  
INHALATION: NASAL/RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS,  
FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, & ASPHYX  
IATION.  
INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, &  
DIARRHEA.

Explanation of Carcinogenicity:BENZENE IS SUSPECTED TO BE AN A2 HUMAN  
CARCINOGENE.

Effects of Overexposure:INGESTION: ASPIRATION OF MATERIAL INTO THE  
LUNGS CAN CAUSE CHEMICAL PNEUMONITIS & FATAL. SKIN: DEFATTING &  
DERMATITIS. EYES: BLURRED VISION. INHALATION: NASAL/RESPIRATORY  
IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,  
UNCONSCIOUSNESS, & ASPHYXIATION.

=====  
= First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:  
WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR  
OXYGEN IF NEEDED. INGESTION: DON'T INDUCE VOMITING. KEEP  
WARM/QUIET. AVOID A SPIRATION OF MATERIAL INTO THE LUNGS DUE TO  
VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:-40F  
Autoignition Temp:Aut  
oignition Temp Text:UNKNON  
Lower Limits:1.5%  
Extinguishing Media:REGULAR FOAM, CO2, & DRY CHEMICAL.  
Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE OPERATED IN  
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.  
Unusual Fire/Explosion Hazard:HIGHLY VOLATILE. VAPORS MAY TRAVEL ALONG  
THE GROUND OR BE MOVED BY VENTILATION & IGNITED OR OTHER IGNITION  
SOURCES. FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON PAPER/

VERMICULITE/FLOOR ABSORBENT.

TRANSFER TO HOOD. REMOVE IGNITION SOURCES. STOP SPILL AT SOURCE. DIKE AREA TO PREVENT SPREADING, PUMP TO SALVAGE TANK. TAKE UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT /SHOVEL IN CONTAINER. EVACUATE AREA.

==== Handling and Storage =====

Handling and Storage Precautions:EMPTY CONTAINERS ARE HAZARDOUS THEY RETAIN RESIDUES (VAPOR, LIQUID, OR SOLID). AVOID CONTACT W/EYES & SKIN.

Other Precautions:DON'T TRANSFER TO UNLABELED CONTAINER. USE & STORE W/ADEQUATE VENTILATION. DON'T USE CUTTING, WELDING TORCH ON & NEAR DRUM BECAUSE PRODUCT RESIDUE CAN IGNITE EXPLOSIVELY.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:IF >TLV, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. IMPLEMENT ENGINEERING/ADMINISTRATIVE CONTROLS. OSHA PERMITS NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS.

Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST/MECHANICAL VENTILATION TO KEEP