

UNIROYAL PLASTICS CO INC -- 3299 BRUSHABLE LACQUER -- 8030-00-166-8813

=====
Product Identification
=====

Product ID:3299 BRUSHABLE LACQUER

MSDS Date:05/20/1988

FSC:8030

NIIN:00-166-8813

MSDS Number: BJYSF

=== Responsible Party ===

Company Name:UNIROYAL PLASTICS CO INC

Address:312 N HILL ST

Box:2000

City:MISHAWAKA

State:IN

ZIP:46544-1399

Country:US

Info Phone Num:219-256-8000

Emergency Phone Num:2

19-256-8000

CAGE:89616

=== Contractor Identification ===

Company Name:UNIROYAL PLASTICS CO INC

Address:312 N HILL ST

Box:2000

City:MISHAWAKA

State:IN

ZIP:46544-1399

Country:US

CAGE:89616

=====
Composition/Information on Ingredients
=====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 0.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:POLYMER SYSTEM

Fraction by Wt: 16.0%

Other REC Limits:NONE SPECIFIED

Ingr

ed Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 83.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:2-BUTANONE VAPORS ARE IRRITATING TO EYES, NOSE & THROAT. HIGH CONCENTRATIONS CAUSE NAUSEA OR NARCOSIS. LIQUID CAN CAUSE DERMATITIS.

=====
= First Aid Measures =====

First Aid:IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR AND IF BREATHING STOPPED, GIVE ARTIFICIAL RESPIRATION. CALL A PHYSICIAN. FOR SKIN CONTACT, WASH WITH SOAP AND WATER. FOR EYE CONTACT, FLUSH WITH WATER AND CALL A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:22F/-6C

Lower Limits:1.4

Upper Limits:11.4

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:FIREFIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. PRODUCT VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND BE IGNITED AT LOCATIONS REMOTE FROM THE HANDLING POINT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. CONTAIN SPILL WITH EARTH AND SOAK UP WITH ABSORBENT MATERIAL AND T

HEN DISPOSE OF
IN A CLOSED CONTAINER APPROPRIATELY MARKED.

=====
Handling and Storage
=====

Handling and Storage Precautions:CAUTION:FLAMMABLE MATERIAL. STORE AND USE AWAY FROM ALL SOURCES OF HEAT, FLAME OR SPARKS.
Other Precautions:USE WITH ADEQUATE VENTILATION. AVOID PROLONGED BREATHING OF VAPORS. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. KEEP OUT OF REACH OF CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:AT CONCENTRATIONS EXCEEDING THE TLV, APPROPRIATE APPROVED RESPIRATORY PROTECTION EQUIPMENT MUST BE USED.
Ventilation:LOCAL EXHAUST AS NEEDED TO KEEP EMPLOYEE EXPOSURE BELOW TLV.
Protective Gloves:YES, SOLVENT (MEK) IMPERVIOUS TYPE.
Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELDS
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F3
Boiling Pt:B.P. Text:175F,79C
Vapor Pres:70MM @ 68F
Vapor Density:2.5
S
pec Gravity:0.86
Evaporation Rate & Reference:5.6 (BU ACETATE = 1)
Solubility in Water:FOR MEK APPROX 25%
Appearance and Odor:BLACK LIQUID WITH KETONE (MEK) ODOR
Percent Volatiles by Volume:88

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS.
Hazardous Decomposition Products:HYDROGEN CHLORIDE, OXIDES OF CARBON AND NITROGEN AND POSSIBLE CYANIDE COMPOUNDS.

=====
Disposal Considerations
=====

=====

Waste Disposal Methods:WASTE 3299 LACQUER WOULD BE CONSIDERED AN EPA HAZARDOUS WASTE D001 & F005. DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.