View NSN Online: https://aerobasegroup.ae/nsn/6810-00-422-2169

TERRA TECHNOLOGIES, INC. -- CALCIUM HYDROXIDE, ANHYDROUS -- 6810-00-422-2169

Product ID:CALCIUM HYDROXIDE, ANHYDROUS

MSDS Date:05/01/1991

FSC:6810

NIIN:00-422-2169

MSDS Number: BJYXG === Responsible Party ===

Company Name: TERRA TECHNOLOGIES, INC.

Box:73087

City:HOUSTON

State:TX ZIP:77273 Country:US

Info Phone Num:800-327-7817

Emergency Phone Num:800-327-7817

CAGE :LO355

=== Contractor Identification ===

Company Name: CARETAKER PRODUCTS

Address:5501 RUSCHE NW Box:City:COMSTOCK PARK

State:MI ZIP:49321 Country:US

Phone:616-784-4875

CAGE:0A9D7

Company Name:FLOR-DRI SUPPLY CO. Address:5450 W JEFFERSON AVENUE

Box:City:DETROIT

State:MI ZIP:48209 Country:US

Phone:313-843-6460

CAGE:0GDX2

Company Name: HANLON CHEMICAL CO INC

Address:1016 S COY

Box:5004

City: KANSAS CITY

State:KS ZIP:66119 Country:US

Phone:913-621-1234

CAGE:17351

Company Name: TERRA TECHNOLOGIES, INC.

Box:73087 City:HOUSTON

State:TX ZIP:77273 Country:US

Phone:800-327-7817

CAGE:LO355

Company Name: TETRA TECHNOLOGIES, INC.

Box:City:HOUSTON

State:TX ZIP:77273 Country:US

Phone:800-327-7817

CAGE:5N055

====== Composition/Information on Ingredients ========

Ingred Name: CALCIUM CHLORIDE

CAS:10043-52-4 RTECS #:EV9800000 Fraction by Wt: 94-97%

Other REC Limits: NONE RECOMMENDED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 3-6%

Other REC Limits: NONE RECOMMENDED

=====

======= Hazards Identification ============

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY CAUSE SEVERE EYE IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. INGESTION IS NOT A MAJOR HEALTH RISK FACTOR. INHALATION OF DUST MAY CAUSE UPPER RESPIRATORY TRACT IRRITATIO N. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES-SEVERE IRRITATION, REDNESS, SWELLING, TEARING. SKIN-IRRITATION, REDNESS, SWELLING, ITCHING. INHALED-IRRITATION, SNEEZING, COUGHING, WHEEZING, SHORTNESS OF BREATH. INGESTED-NO INFORMATION FOUND.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

======= First Aid Measu

First Aid:EYES-IRRIGATE WITH LOTS OF WATER FOR 15 MINUTES. SKIN-WASH OFF WITH RUNNING WATER FOR 15 MINUTES. INHALED-REMOVE PERSON TO FRESH AIR. TREAT SYMPTOMATICALLY. INGESTED-IF CONSCIOUS, INDUCE VOMITING. GET MEDICAL ATTENTION.

=========== Fire Fighting Measures ================

Extinguishing Media: NON-COMBUSTIBLE; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BR

EATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:NONE.

======== Accidental Release Measures ===========

Spill Release Procedures: SWEEP UP GRANULES AND FLUSH AREA WITH LOTS OF WATER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

============ Handling and Storage ===========================

Handling and Storage Precautions: STORE IN A COOL, DRY PLACE. USE WITH ADEQUATE VENTILATION. DO NOT GET IN EYES.

Other Precautions: NONE SPECIFIE

D BY MANUFACTURER.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE NORMALLY REQUIRED.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: RUBBER.

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices: WASH HANDS AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health

INCOMPATIBLE MATERIALS:WATER, METHYL VINYL ETHER, ZINC, BROMINE TRIFLUORIDE, MIXTURES OF LIME AND BORIC ACID, BARIUM CHLORIDE, 2-FURAN PERCARBOXYLIC ACID, METALS (WILL SLOWLY CORRODE), ALUMINUM AND AL UMINUM ALLOYS, YELLOW BRASS.

======== Physical/Chemical Properties ===========

HCC:N1 Boiling Pt:B.P. Text:3515F,1935C Spec Gravity:50-55 LB/FT3 Solubility in Water:APPR ECIABLE

Appearance and Odor:SMALL, WHITE, HYDROSCOPIC, DELIQUESCENT GRANULES; NO ODOR.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

AQUEOUS SOLUTIONS WILL CORRODE METALS; ADDITION OF ALKALINE COMPOUNDS WILL RELEASE AMMONIACAL VAPORS.

Stability Condition to Avoid: WILL ABSORB WATER.

Hazardous Decomposition Products: NONE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

==== Disposal Considerations ====

Waste Disposal Methods:WASH AWAY WITH LARGE EXCESS OF WATER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person ut ilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.